

DEPENDENT RESURVEY, W. BDY., T. 24 S., R. 3 W.

CHAINS

Set an iron post, 3 ft. long, 2 ins. diam., 29 ins. in the ground, with brass cap mkd.

T 24 S	T 24 S
R 4 W	S 7
S 13	S 18
	R 3 W
	1950

from which

A fir, 30 ins. diam., bears N. $35\frac{1}{2}^{\circ}$ E., 104 lks. dist., mkd. T 24 S R 3 W S 7 BT.

A cedar, 20 ins. diam., bears S. 85° E., 93 lks. dist., mkd. T 24 S R 3 W S 18 BT.

The section corner is located on the east shoulder of a graded dirt logging road.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, maple, alder, madrona, yew, chinquapin and dogwood.

Undergrowth, vinemapple, salmonberry, salal, bracken, arrowwood, hazel, willow, thimbleberry and huckleberry.

N. $1^{\circ}17'$ E., along the W. bdy. of sec. 7.

Asc. 86 ft. over SE. slope, through heavy timber and dense undergrowth, in partially logged area.

1.20 A graded dirt logging road, bears N: 20° E. and S. 10° W.

6.26 Point for the closing cor. of secs. 12 and 13, T. 24 S., R. 4 W., on the W. bdy. of sec. 7.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 24 S	T 24 S
S 12	R 3 W
C C	S 7
S 13	
R 4 W	
	1950

from which

A fir, 20 ins. diam., bears N. 54° W., 73 lks. dist., mkd. T 24 S R 4 W S 12 CC BT.

A fir, 8 ins. diam., bears S. $81\frac{1}{2}^{\circ}$ W., 47 lks. dist., mkd. T 24 S R 4 W S 13 CC BT.

From this corner Thiel's original closing corner of secs. 12 and 13 bears East, 62 lks. dist., determined at the record distance from each of the original bearing trees which stand as follows:

A fir, 20 ins. diam., bears N. 6° W., 47 lks. dist., with the scribe marks BT visible in the partially opened old blaze. (Record bearing N. 5° W.) I add the marks AM on this old bearing tree.

A cedar, 24 ins. diam., bears S. 72° W., 33 lks. dist., with the scribe marks BT visible in the partially opened old blaze. (Record bearing S. 73° W.) I add the marks AM on this old bearing tree.

Continue to ascend 106 ft. over SE. slope.