

DEPENDENT RESURVEY, W. BDY., T. 24 S., R. 3 W.

CHAINS 13.40	A spur, slopes S. 60° E.; desc. 3 ft. over NE. slope.
14.80	A ravine, course SE.; asc. 73 ft. over SE. slope.
19.30	A spur, slopes E.; desc. 45 ft. over NE. slope.
21.50	A branch, 2 lks. wide, course S. 60° E.; asc. 114 ft. over broken S. slope.
25.60	A graded dirt logging road, bears N. 60° W. and N. 60° E., at curve.
27.40	A spur, slopes E.; desc. 18 ft. over NE. slope.
30.90	A ravine, course E.; asc. 23 ft. over SE. slope.
32.80	Foot of spur, slopes S. 60° E.; desc. 9 ft. over NE. slope.
33.65	A branch, 2 lks. wide, course SE.; asc. 76 ft. over broken S. slope.
39.035	Point for the $\frac{1}{4}$ sec. cor. of sec. 7, T. 24 S., R. 3 W., at mid-point on the W. bdy. of sec. 7. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$ S 7 1950
	from which
	A fir, 32 ins. diam., bears N. 50° E., 35 lks. dist., mkd. $\frac{1}{4}$ S 7 BT.
	A cedar, 16 ins. diam., bears S. 67° E., 4 lks. dist., mkd. $\frac{1}{4}$ S 7 BT.
	Continue to ascend 112 ft. over broken S. slope.
44.00	A spring branch, 1 lk. wide, course S. 30° E.
45.265	Point for the $\frac{1}{4}$ sec. cor. of sec. 12, T. 24 S., R. 4 W., at mid-point on the E. bdy. of sec. 12. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$ S 12 1950
	from which
	A hemlock, 20 ins. diam., bears N. 50 $\frac{1}{2}$ ° W., 46 lks. dist., mkd. $\frac{1}{4}$ S 12 BT.
	A cedar, 16 ins. diam., bears S. 64° W., 82 lks. dist., mkd. $\frac{1}{4}$ S 12 BT.
	Continue to ascend 245 ft. over broken S. slope.
54.70	A spur, slopes SE.; thence over E. slope.
60.25	A branch, 2 lks. wide, course SE.; asc. 254 ft. over broken S. slope.
70.70	A spur, slopes SE.; continue to ascend 25 ft. over SE. slope.
78.07	Point for the cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.