

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF T. 24 S., R. 3 W.

CHAINS

Undergrowth, vinemaple, arrowwood, willow, slickleaf, bracken, salal, salmonberry, thimbleberry, hazel, ninebark and hardhack.

The corner of secs. 15, 16, 21 and 22 was remonumented by the county surveyor and duly recorded in the records of Douglas County, Oregon with an automobile spring leaf, 3 ft. long, 2 ins. wide, 5/16 in. thick; and has been locally recognized and accepted for many years. I therefore accept this cor. for control of this resurvey.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

FD OK
M/36-37
D Baker
11/2000

T 24	S R 3 W
S 16	S 15
S 21	S 22
1950	

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. 88°51' W., bet. secs. 16 and 21.

Asc. 16 ft. over SE. slope, through logged and burned area.

3.18 A graded and graveled logging road, bears N. 78° E. and S. 70° W.

4.00 Top of ascent on S. slope; desc. 27 ft. over rolling broken S. slope.

8.20 A branch, 1 lk. wide, course S.

18.10 A branch, 3 lks. wide, course S. 10° E.

22.80 A branch, 10 lks. wide, course S. 10° E.; asc. 138 ft. over SE. slope.

33.20 An unimproved dirt road, bears N. 30° W. and S. 30° E.

35.20 A spur, slopes S.; desc. 21 ft. over SW. slope.

38.425 Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4	S 16
	S 21
1950	

from which

A fir, 26 ins. diam., bears N. 71/2° W., 53 lks. dist., mkd. 1/4 S 16 BT.

A fir, 14 ins. diam., bears S. 48 1/4° E., 41 lks. dist., mkd. 1/4 S 21 BT.

Desc. 2 ft. over SW. slope.

40.20 A branch, 2 lks. wide, course S.; asc. 103 ft. over SE. slope.

46.75 A spur, slopes S.; desc. 286 ft. over SW. slope.

60.90 Coon Creek, 30 lks. wide, course SE.; asc. 53 ft. over NE. slope.