

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF T. 24 S., R. 3 W.

CHAINS	
	Desc. 42 ft. over SW. slope, through heavy timber and dense undergrowth, in logged area.
3.60	A branch, 3 lks. wide, course N. 80° W.; asc. 71 ft. over NE. slope.
6.20	An abandoned dirt logging road, bears N. 60° W. and S. 60° E.
9.00	A spur, slopes N. 20° W.; desc. 208 ft. over NW. slope.
14.40	An abandoned dirt logging road, bears NE. and SW.
24.80	Weyerhaeuser Timber Company's logging railroad, bears N. 30° E. and S. 30° W.
25.15	A telephone line, bears N. 30° E. and S. 30° W.
26.15	Calapooya Creek, 35 lks. wide, course SW.; asc. 36 ft. over partially cleared rolling bottom land.
31.25	A graded and graveled county road, bears N. 30° E. and S. 30° W.
31.55	A branch, 5 lks. wide, course S. 70° E.
35.38	A power line, bears N. and S.
39.71	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 20 and 29, remonumented by the county surveyor with an unmarked iron bar, 3 ft. long, <math>1\frac{1}{4}</math> ins. sq.; from which the remains of the original bearing trees:</p> <p>A sawed cedar stump, 42 ins. diam., bears N. 31° W., 8 lks. dist., mkd. by the county surveyor <math>\frac{1}{4}</math> S 20 T 24 S R 3 W CS BT. (Record N. 20° W., 8 lks. dist.)</p> <p>A dogwood stool, bears S. 14° E., 9 lks. dist. on which no marks remain. (Record South, 9 lks. dist.)</p> <p>and new bearing trees mkd. by the county surveyor:</p> <p>A fir, 12 ins. diam., bears N. 84<math>\frac{1}{2}</math>° W., 21 lks. dist., with blaze healed.</p> <p>A fir, 12 ins. diam., bears S. 46° W., 23 lks. dist., with blaze healed.</p> <p>At the corner point</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: right; margin-right: 50px;"> <math>\frac{1}{4}</math> S 20  <math>\frac{1}{4}</math> S 29                      1950                 </div> <div style="text-align: right; margin-right: 50px; font-style: italic;">                     FND. OK 6/91                      D. PEEL M 113-43                      FND. OK 6/96                      D. BAKER M 125-33                 </div> <p>from which</p> <p>A fir, 14 ins. diam., bears N. 76<math>\frac{1}{2}</math>° W., 37 lks. dist., mkd. <math>\frac{1}{4}</math> S 29 BT. (error in record, should be S 20)</p> <p>Reset the county surveyor's iron bar alongside the iron post.</p> <p style="text-align: center;">—————</p> <p>N. 81°48' W., beginning new measurement.</p> <p>Asc. 143 ft. over rolling broken E. slope, through heavy timber and dense undergrowth, in partially logged area.</p>
13.65	Top of ascent on N. slope; desc. 15 ft. over NW. slope.
15.80	Spring, flows NE.; foot of descent on N. slope; asc. 60 ft. over rolling broken NE. slope.