


11484

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF T. 24 S., R. 3 W.

CHAINS

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.



from which

A fir, 12 ins. diam., bears N. 62 $\frac{1}{4}$ ° E., 43 lks. dist., mkd. $\frac{1}{4}$ S 20 BT.

An incense cedar, 36 ins. diam., bears S. 46 $\frac{1}{4}$ ° W., 82 lks. dist., mkd. $\frac{1}{4}$ S 19 BT.

N. 6°39' E., beginning new measurement.

Desc. 544 ft. over broken N. slope.


17.60 A branch, 6 lks. wide, course E.; asc. 347 ft. over broken S. slope.

19.25 An abandoned dirt logging road, bears N. 78° W. and S. 77° E.

31.00 A spur, slopes S. 55° E.; desc. 163 ft. over NE. slope.

39.08 Point for the cor. of secs. 17, 18, 19 and 20, at proportional distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.



from which

An iron post, 3 ft. long, 2 ins. diam., set 28 ins. in the ground, for a reference monument, bears S. 45° E., 30 lks. dist., with brass cap mkd. T 24 S R 3 W S 20 RM 1950 and an arrow pointing to the true cor.

An iron post, 3 ft. long, 2 ins. diam., set 28 ins. in the ground, for a reference monument, bears N. 45° W., 30 lks. dist., with brass cap mkd. T 24 S R 3 W S 18 RM 1950 and an arrow pointing to the true cor.

Land, mountainous.

Soil, heavy sandy clay loam.

Timber, fir, hemlock, cedar, maple, alder, chinquapin, dogwood, yew and madrona.

Undergrowth, vinemaple, willow, arrowwood, hazel, bracken, salal, thimbleberry, slickleaf, manzanita and huckleberry.

From the cor. of secs. 16, 17, 20 and 21

N. 86°55' W., bet. secs. 17 and 20.

Asc. 44 ft. over SE. slope, through heavy timber and dense undergrowth, in logged area.

3.75 A spur, slopes SE.; desc. 15 ft. over SW. slope.

5.00 Foot of descent on S. slope; asc. 43 ft. over SE. slope.