

11490

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF T. 24 S., R. 3 W.

CHAINS

Thence over broken E. slope.

41.90 A branch, 6 lks. wide, course S. 30° E.; asc. 169 ft. over S. slope, changing to SE. slope.

53.00 Top of ascent on E. slope; desc. 16 ft. over NE. slope.

55.60 A branch, 5 lks. wide, course SE.; asc. 223 ft. over broken S. slope.

77.65 Point for the cor. of secs. 5, 6, 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 24 S R 3 W
S 6 S 5

S 7 S 8
1950

from which

A fir, 22 ins. diam., bears N. 88°45' E., 40 lks. dist., mkd. T 24 S R 3 W S 5 BT.

A fir, 54 ins. diam., bears S. 45½° E., 9 lks. dist., mkd. T 24 S R 3 W S 8 BT.

A yew, 12 ins. diam., bears S. 4½° W., 56 lks. dist., mkd. T 24 S R 3 W S 7 BT.

A cedar, 20 ins. diam., bears N. 9½° W., 70 lks. dist., mkd. T 24 S R 3 W S 6 BT.

Land, mountainous.

Soil, sandy and rocky clay loam.

Timber, fir, hemlock, cedar, alder, maple, yew, chinquapin, madrona and dogwood; undergrowth, vinemapple, arrowwood, willow, hazel, bracken, slickleaf, salmonberry, thimbleberry, manzanita and salal.

From the cor. of secs. 4, 5, 8 and 9

N. 89°34' W., bet. secs. 5 and 8.

Asc. 479 ft. over NE. slope, changing to E. slope, through heavy timber and dense undergrowth.

17.20 A graded and graveled logging road, bears N. 15° W. and S. 15° E.

22.50 A spur ridge, bears N. and S.; desc. 437 ft. over broken W. slope.

37.45 A ravine, course S.; asc. 43 ft. over SE. slope.

38.865 Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

S 5
¼ S 8

1950

from which

A fir, 15 ins. diam., bears N. 49¼° W., 32 lks. dist., mkd. ¼ S 5 BT.