

Dependent Resurvey of the S. Bdy. of T. 25 S., R3 W.

CHAINS

An incense cedar, 8 ins. diam., bears N.31 3/4°W., 35 lks. dist., mkd. T 25 S R 4 W S 36 C S B T. (County surveyor's B.T.)

An incense cedar, 18 ins. diam., bears N.14 3/4°E., 59 lks. dist., mkd. T 25 S R 3 W S 31 B T. (New B.T.)

A Douglas fir, 12 ins. diam., bears S.37°E., 20 lks. dist., mkd. T 26 S R 3 W S 6 B T. (New B.T.)

An incense cedar, 20 ins. diam., bears S.87 3/4°W., 146 lks. dist. mkd. T 26 S R 4 W S 1 B T. (New B.T.)

The geographic position of this corner is latitude 43° 20 3/4' N., and longitude 123° 06 1/2' W.

Thence

S. 88° 39' E., bet. secs. 6 and 31.

Desc. 107 ft. over rolling E. slope, through heavy timber and dense undergrowth.

6.10 Enter bottom land, bears N. and S.

7.15 A branch, 10 lks. wide, course S.

9.40 Leave bottom land, bears N. and S.; asc. 302 ft. over broken W. slope.

20.50 A spur, slopes S.; desc. 243 ft. over broken E. slope.

35.85 A branch, 2 lks. wide, course S.; 9 ft. over broken SE. slope.

38.45 A branch, 8 lks. wide, course S.; asc. 17 ft. over broken NW. slope.

38.79 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S31}{S6} \\ 1943$$

from which

A fir, 20 ins. diam., bears N.26°E., 11 lks. dist., mkd. 1/4 S 31 B T.

A fir, 20 ins. diam., bears S.61°W., 6 lks. dist., mkd. 1/4 S 6 B T.

Asc. 660 ft. over broken NW. slope.

68.80 A spur, ridge, bears NE. and SW.; desc. 207 ft. over SE. slope.

72.60 A graded dirt road, bears NE. and SW.

78.81 Point for original cor. of secs. 5, 6, 31, and 32, determined by reference to the record measurements from the original NE., SW., and NW. bearing trees.

At point for corner.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 5, 6, 31, and 32, with brass cap mkd.