

County Surveyor's Record, Douglas County, Oregon

11502

4

Dependent Resurvey of the S. Bdy. of T. 25 S., R. 3 W;

CHAINS

T25S R3W
S31 | S32
 S6 | S5
 T26S
 1943

from which

- A maple, 14 ins. diam., bears N.63½°E., 13 lks. dist. with old blaze decayed. (Old B.T.)
- A fir, 40 ins. diam., bears S.60°W., 7 lks. dist., mkd. on bark T 26 S R 3 W S 6 B T. (Old B.T.)
- A dogwood, 7 ins. diam., bears N.9°W., 19 lks. dist., with blaze healed. (Old B.T.)
- A fir, 60 ins. diam., bears N.12 3/4°E., 65 lks. dist. mkd. T 25 S R 3 W S 32 B T. (New B.T.)
- A fir, 20 ins. diam., bears S.58½°E., 66 lks. dist., mkd. T 26 S R 3 W S 5 B T. (New B.T.)
- A fir, 22 ins. diam., bears N.66½°W., 64 lks. dist., mkd. T 25 S R 3 W S 31 B T. (New B.T.)

Land, mountainous and level.
 Soil, sandy loam and clay; 1st and 2d. rate.
 Timber, fir, cedar, oak, maple, madrona, and dogwood.
 Undergrowth, vinemaple, poison oak, lilac, arrowwood, willow, syringa, slickleaf, and bracken.

N. 89° 18' E., bet. secs. 5 and 32.

Desc. 125 ft. over SE. slope, through heavy timber and dense undergrowth.

14.40 A branch, 20 lks. wide, course S.; asc. 109 ft. over SW. slope.

18.40 An ungraded road, bears N. and S.
 39.40 Point for original ¼ sec. cor., determined by reference to the record measurements from the original bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, for ¼ sec. cor., with brass cap mkd.

¼ S32
 S5
 1943

from which

- A white oak, dead and down, 12 ins. diam., bears North, 42 lks. dist., with blaze decayed. (Old B.T.)
- A black oak, 16 ins. diam., bears S.27°E., 90 lks. dist. with blaze decayed. (Old B.T.)
- A fir, 15 ins. diam., bears N.83½°E., 24 lks. dist., mkd. ¼ S 32 B T. (New B.T.)
- A fir, 13 ins. diam., bears S.22½°E., 19 lks. dist., mkd. ¼ S 5 B T. (New B.T.)

Thence

S. 89° 01' E., with new measurement.