

County Surveyor's Record, Douglas County, Oregon

11504

Dependent Resurvey of the S. Bdy. of T. 25 S., 3 W.

CHAINS	
	S. 89° 11' E., bet, secs. 4 and 33.
	Asc. 390 ft. over SW. slope changing to broken W. slope, through heavy timber and dense undergrowth.
18.30	A trail and telephone line, bears N.30°E., and S.30°W.
18.50	A spur, slopes S.; desc. 22 ft. over SE. slope.
22.70	Foot of descent on S. slope; asc. 216 ft. over SW. slope.
36.30	Top of bluff, 40 ft. high, bears NW. and SE.
40.08	Point for original $\frac{1}{4}$ sec. cor., determined at the record bearing and distance from the original SE. bearing tree,
	At point for corner,
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \text{ S33} \\ \hline \text{S4} \\ 1943 \end{array}$
	from which
	A fir, 40 ins. diam., bears S.85°E., 173 lks. dist., on which I uncovered the scribe marks $\frac{1}{4}$ S beneath 88 years overgrowth. (Old B.T.)
	A fir, 12 ins. diam., bears N.52 $\frac{3}{4}$ °W., 27 lks. dist., mkd. $\frac{1}{4}$ S 33 B T. (New B.T.)
	A fir, 12 ins. diam., bears S.10 $\frac{3}{4}$ °W., 16 lks. dist., mkd. $\frac{1}{4}$ S 4 B T. (New B.T.)
	Thence
	S. 88° 59' E., with new measurement.
	Asc. 198 ft. over broken SW. slope.
5.05	A spring branch, 3 lks. wide, course S.
12.60	" " 3 " " " S.
22.30	" " 2 " " " S.
27.60	A spur, slopes S.; desc. 297 ft. over broken E. slope.
40.18	The original cor. of secs. 3, 4, 33, and 34, a badly decayed yew stake, 3 $\frac{1}{2}$ ft. long, 4 ins. square, on which only ax marks remain.
	At point for corner,
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the remains of decayed stake deposited at the base, for cor. of secs, 3, 4, 33, and 34, with brass cap mkd.
	$\begin{array}{r} \text{T25S R3W} \\ \hline \text{S33 S34} \\ \hline \text{S4 S3} \\ \text{T26S} \\ 1943 \end{array}$
	from which
	A maple, 12 ins. diam., bears N.57°E., 18 lks. dist. with old blaze decayed. (Old B.T.)