

Dependent Resurvey of the E. Bdy. of T. 25 S., R. 3 W.

CHAINS

"Reestablishment of the survey executed by Laban H. Wheeler, Deputy Surveyor, in 1883, of which there is a record of a retracement by Hezekiah H. Johnson, Deputy Surveyor, in 1900."

After careful investigation, it is developed that Johnson's recorded retracement of this line is entirely fictitious, that it is a deliberate fabrication on his part for the purpose of justifying his own work and creating a limiting boundary for T. 25 S., R. 2 W., and is therefore rejected as a suitable basis for restoration of lost corners referring to T. 25 S., R. 3 W.

From the cor. of Tps. 25 and 26 S., Rs. 2 and 3 W.

N. 2° 00' E., along E. bdy. of sec. 36.

Desc. 348 ft. over broken W. slope, changing to precipitous NW. slope, through heavy timber and dense undergrowth.

28.60 Rock Creek, 140 lks. wide, course S.70°W.; asc. 16 ft. over rolling bottom land.

34.50 McComas Creek, 12 lks. wide, course SE.; asc. 75 ft. over S. slope.

37.00 A graded and graveled road, and telephone line, bears NE. and SW.

44.20 A spur, slopes S.60°E.; desc. 5 ft. over NE. slope.

44.56 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 36 only, with brass cap mkd.

$\frac{1}{4}$  S36

1943

from which

A fir, 9 ins. diam., bears S.8 $\frac{1}{2}$ °W., 7 lks. dist., mkd.  $\frac{1}{4}$  S 36 B T.

A fir, 13 ins. diam., bears N.38°W., 9 lks. dist., mkd.  $\frac{1}{4}$  S 36 B T.

Desc. 40 ft. over NE. slope, changing to rolling E. slope.

55.25 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 31 only, with brass cap mkd.

$\frac{1}{4}$  S31

1943

from which

A fir, 26 ins. diam., bears N.6 $\frac{1}{2}$ °E., 94 lks. dist., mkd.  $\frac{1}{4}$  S 31 B T.

A fir, 6 ins. diam., bears S.52°E., 9 lks. dist., mkd.  $\frac{1}{4}$  S 31 B T.