

County Surveyor's Record, Douglas County, Oregon

11510

12

Dependent Resurvey of the E. Bdy. of T. 25 S., R. 3 W.

CHAINS	Desc. 5 ft. over rolling broken E. slope.												
64.10	Kelly Creek, 30 lks. wide, course SE.; asc. 115 ft. over broken S. slope.												
75.00	An irrigation ditch, 5 lks. wide, flows N.75°E.												
83.56	<p>The original closing cor. of secs. 30 and 31, a basalt stone, 16x10x4 ins., firmly set, mkd. with 5 grooves on N., 1 groove on S., and C C on E. face.</p> <p>At point for corner,</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone deposited at the base, for closing cor. of secs. 30 and 31, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">T25S</td> <td style="padding: 2px 5px;">T25S</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">R3W</td> <td style="padding: 2px 5px;">S30</td> <td style="padding: 2px 5px;">CC</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S36</td> <td style="padding: 2px 5px;">S31</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;"></td> <td style="padding: 2px 5px;">R2W</td> <td></td> </tr> </table> <p>1943</p> </div> <p style="text-align: right; margin-right: 50px;">from which</p> <p>A fir, 30 ins. diam., bears N.73°E., 55 lks. dist., with blaze healed. (Old B.T.)</p> <p>A fir, 16 ins. diam., bears S.61°E., 103 lks. dist., mkd. T 25 S R 2 W S 31 C C B T. (New B.T.)</p> <p>Asc. 6 ft. over gentle S. slope, changing to gentle E. slope.</p>	T25S	T25S		R3W	S30	CC	S36	S31			R2W	
T25S	T25S												
R3W	S30	CC											
S36	S31												
	R2W												
89.12	<p>The original sec. cor. which now refers to secs. 25 and 36 only, a basalt stone, 10x8x8 ins., firmly set in a small ring of stone, mkd. with 5 chaining pin scratches on N. and one chaining pin scratch on S. face.</p> <p>At point for corner,</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the original stone deposited at the base, for cor. of secs. 25 and 36, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">T25S</td> <td style="padding: 2px 5px;">T25S</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S25</td> <td style="padding: 2px 5px;">R2W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S36</td> <td style="padding: 2px 5px;">S30</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">R3W</td> <td style="padding: 2px 5px;"></td> </tr> </table> <p>1943</p> </div> <p style="text-align: right; margin-right: 50px;">from which</p> <p>A Douglas fir, 14 ins. diam., bears N.69°E., 27 lks. dist., on which I uncover and efface the inscription T 25 S R 2 W S 30 B T which I find beneath 60 years overgrowth. (A Wheeler B.T.)</p> <p>A hemlock, 14 ins. diam., bears S.67½°E., 41 lks. dist., on which I uncover and efface the inscription T 25 S R 2 W S 31 B T which I find beneath 60 years overgrowth. (A Wheeler B.T.)</p> <p>A hemlock 12 ins. diam., bears S.51½°W., 58 lks. dist., on which I uncover the scribe marks B T beneath 60 years overgrowth. (A Wheeler B.T.)</p> <p>A hemlock 24 ins. diam., bears N.61½°W., 31 lks. dist., with old blaze healed. (A Wheeler B.T.)</p> <p>A red cedar, 30 ins. diam., bears S.43°W., 86 lks.</p>	T25S	T25S	S25	R2W	S36	S30	R3W					
T25S	T25S												
S25	R2W												
S36	S30												
R3W													