

Dependent Resurvey of the E. Bdy. of T. 25 S., R. 3 W.

CHAINS

N. 1° 12' E., along E. bdy. of sec. 24.

Asc. 21 ft. over SE. slope, through heavy timber and dense undergrowth.

4.00 A spur, slopes E.; desc. 343 ft. over NE. slope.

13.40 Top of bluff, 60 ft. high, bears NW. and SE,


18.90 A marshy branch, 3 lks. wide, course E.; asc. 12 ft. over SE. slope.

21.20 Top of ascent on E. slope; desc. 21 ft. over NE. slope.

22.00 A branch, 10 lks. wide, course E.; asc. 79 ft. over SE. slope.

34.285 Mid-point on the W. bdy. of sec. 19.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 19 only, with brass cap mkd.



from which

A fir, 32 ins. diam., bears N.22°E., 55 lks. dist., mkd. $\frac{1}{4}$ S 19 B T.


A fir, 30 ins. diam., bears S.21°E., 43 lks. dist., mkd. $\frac{1}{4}$ S 19 B T.

Asc. 23 ft. over SE. slope.

40.86 Point for original $\frac{1}{4}$ sec. cor. which now refers to sec. 24 only, determined by reference to the record measurements from both old bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 24 only, with brass cap mkd.



from which

A red cedar, 22 ins. diam., bears S.48 $\frac{1}{2}$ °E., 27 lks. dist., mkd. $\frac{1}{4}$ S B T. I obliterate the marks on this old bearing tree.

A maple, 11 ins. diam., bears N.16°W., 17 lks. dist., with old blaze healed. (Old B.T.)

A fir, 50 ins. diam., bears S.79 $\frac{1}{2}$ °W., 41 lks. dist., mkd. $\frac{1}{4}$ S 24 B T. (New B.T.)

A fir, 36 ins. diam., bears N.15 $\frac{1}{2}$ °W., 49 lks. dist., mkd. $\frac{1}{4}$ S 24 B T. (New B.T.)

Thence

N.0° 01' E., with new measurement.