

Dependent Resurvey of the E. Bdy. of T. 25 S., R. 3 W.

CHAINS

dist., mkd. T 25 S R 3 W S 13 B T. (New B.T.)

Land, mountainous.
 Soil, sandy and rocky loam; 2d and 3d rate.
 Timber, fir, hemlock, cedar, maple, alder, pine, madrona,
 dogwood, chinquapin, and oak.
 Undergrowth, vinemaple, salal, salmonberry, arrowwood,
 willow, hazel, bracken, poison oak, and slickleaf.

N. 1° 19' W., along E. bdy. of sec. 13.

Asc. 68 ft. over SE. slope, through heavy timber and
 dense undergrowth.

11.00 A spur, slopes E.; desc. 29 ft. over NE. slope.


13.90 Foot of descent on E. slope; asc. 44 ft. over SE. slope.

17.30 A spur, slopes E.; desc. 79 ft. over NE. slope.

22.20 A branch, 12 lks. wide, course SE.; asc. 313 ft. over
 SW. slope.

32.105 Mid-point on the W. bdy. of sec. 18.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
 ground, for $\frac{1}{4}$ sec. cor. of sec. 18 only, with brass
 cap mkd.



from which


A hemlock, 22 ins. diam., bears N.77°E., 21 lks. dist.,
 mkd. $\frac{1}{4}$ S 18 B T.

A fir, 54 ins. diam., bears S.18 $\frac{1}{2}$ °E., 65 lks. dist.,
 mkd. $\frac{1}{4}$ S 18 B T.

Asc. 212 ft. over SW. slope.

39.17 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the
 ground, to bedrock, and in a mound of stone to top, for
 $\frac{1}{4}$ sec. cor. of sec. 13 only, with brass cap mkd.



from which

A sugar pine, 12 ins. diam., bears S.13°W., 6 lks.
 dist., mkd. $\frac{1}{4}$ S 13 B T.

A fir, 14 ins. diam., bears N.49 $\frac{1}{2}$ °W., 65 lks. dist.,
 mkd. $\frac{1}{4}$ S 13 B T.

Asc. 628 ft. over broken SW. slope.

50.90 A shallow ravine, course SW.

70.00 Foot of sloping bluff, 80 ft. high, bears NW. and SE,

70.90 Top of bluff, bears NW. and SE.