

Dependent Resurvey of the E. Bdy. of T. 25 S., R. 3 W.

CHAINS
25.30

A spur, slopes E.; desc. 59 ft. over broken NE. slope.


31.00

A spring branch, 1 lk. wide, course E.

32.76

Mid-point on the W. bdy of sec. 7.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 7 only, with brass cap mkd.



from which

A fir, 36 ins. diam., bears S.57 $\frac{1}{2}$ °E., 57 lks. dist., mkd. $\frac{1}{4}$ S 7 B T.

A fir, 30 ins. diam., bears S.81 $\frac{1}{2}$ °E., 50 lks. dist., mkd. $\frac{1}{4}$ S 7 B T.

Desc. 25 ft. over NE. slope.

39.70


A branch, 3 lks. wide, course SE.; asc. 4 ft. over SW. slope.

40.22

Point for original $\frac{1}{4}$ sec. cor. which now refers to sec. 12 only, determined by reference to the record measurements from the original bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 12 only, with brass cap mkd.



from which

A hemlock, 22 ins. diam., bears S.40°E., 19 lks. dist., mkd. $\frac{1}{4}$ S B T. I obliterate the marks on this old bearing tree.

A fir, 26 ins. diam., bears S.78°W., 23 lks. dist., with blaze healed. (Old B.T.)

A fir, 32 ins. diam., bears S.21°W., 17 lks. dist., mkd. $\frac{1}{4}$ S 12 B T. (New B.T.)

Thence

N. 0° 55' E., with new measurement.

Asc. 440 ft. over SW. slope, changing to SE. slope.

27.20

A spur, slopes NE.; desc. 27 ft. over NE. slope.

30.70

Foot of descent on E. slope; asc. 7 ft. over SE. slope.

32.10

Proportional measurement.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 6 and 7, with brass cap mkd.