

11518 County Surveyor's Record, Douglas County, Oregon

20

Dependent Resurvey of the E. Bdy. of T. 25 S., R. 3 W.

CHAINS

T25S	T25S	
R3W	S6	CC
S12	S7	
	R2W	
1943		

from which

A fir, 30 ins. diam., bears N.50 3/4°E., 23 lks. dist., mkd. T 25 S R 2 W S 6 C C B T.

A fir, 32 ins. diam., bears S.20 1/2°E., 21 lks. dist., mkd. T 25 S R 2 W S 7 C C B T.

Asc. 46 ft., over SE. slope.

39.72

Point for original sec. cor. which new refers to secs. 1 and 12 only, determined by reference to the record measurements from all of the original bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 1 and 12, with brass cap mkd.

T25S	T25S
S1	R2W
S12	S6
R3W	
1943	

from which

A fir, 36 ins. diam., bears N.61 1/2°E., 57 lks. dist., mkd. T 25 R 2 S 6 B T. I obliterate the marks on this old bearing tree.

A dead fir, 24 ins. diam., bears S.59°E., 13 lks. dist., mkd. T 25 R 2 S 7 B T. I obliterate the marks on this old bearing tree.

A fir, 40 ins. diam., bears S.9°W., 19 lks. dist., with blaze healed. (Old B.T.)

A fir, 50 ins. diam., bears N.24°W., 33 lks. dist., with blaze healed. (Old B.T.)

Land, mountainous;

Soil, sandy and rocky loam; 2d and 3d rate.

Timber, fir, hemlock, cedar, pine, madrona, chinquapin, maple, and dogwood.

Undergrowth, vinemaple, rhododendron, slickleaf, willow, manzanita, lilac, salal, bracken, and arrowwood.

N. 0° 11' E., along E. bdy. of sec. 1.

Asc. 79 ft. over SE. slope, through heavy timber and dense undergrowth.

5.15

Top of ascent on shoulder of ridge bearing NW. and SW.; desc. 109 ft. over broken NE. slope.

17.30

Head of ravine, course NE.; desc. 304 ft. over NE. slope.

35.00

Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. of sec. 6 only, with brass cap mkd.