


Dependent Resurvey of the E. Bdy. of T. 25 S., R. 3 W.

CHAINS



T25S  
1943

from which

- A hemlock, 20 ins. diam., bears N.70°E., 26 lks. dist., with blaze healed. (Old B.T.)
- A hemlock, 14 ins. diam., bears S.11¼°E., 37 lks. dist., with blaze healed. (Old B.T.)
- A hemlock, 20 ins. diam., bears S.20½°W., 19 lks. dist., mkd. S 1 T 25 S R 3 W B T. (Old B.T.)
- A fir, 48 ins. diam., bears N.50½°W., 64 lks. dist., mkd. on bark S 36 T 24 S R 3 W B T. I re-blaze and re-mark this old bearing tree T 24 S R 3 W S 36 B T.
- A fir, 48 ins. diam., bears S.18½°E., 38 lks. dist., mkd. T 25 S R 2 W S 6 B T. (New B.T.)

Land, mountainous.  
Soil, sandy loam and rocky clay; 2d and 3d rate.  
Timber, fir, hemlock, cedar, pine, alder, maple, madrona, chinquapin, and dogwood.  
Undergrowth, vinemaple, rhododendron, slickleaf, willow, manzanita, salal, bracken, arrowwood, and hazel.

Dependent Resurvey of the W. Bdy. of T. 25 S., R. 3 W.

"Reestablishment of the survey of the N. two miles of which was executed by Gordon and Gardner, Deputy Surveyors, in 1855, and the S. four miles of which was executed by W. H. Byars, Deputy Surveyor, in 1871."

From the cor. of Tps. 25 and 26 S., Rs. 3 and 4 W., heretofore described

N. 0° 22' E., bet. secs. 31 and 36.

Desc. 37 ft. over rolling broken E. slope, through heavy timber and dense undergrowth.

10.15 A branch, 3 lks. wide, course E.; asc. 338 ft. over SE. slope.

34.00 A spur, slopes E.; desc. 109 ft. over NE. slope.

40.11 Point for original ¼ sec. cor., determined at the record measurements from both old bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd.



1943

from which