

11522 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the W. Bdy. of T. 25 S., R. 3 W.

CHAINS

17.30

A spur, slopes SW.; desc. 45 ft. over NW. slope.

24.30

Foot of descent on W. slope; asc. 84 ft. over SW. slope.

30.60

A spur, slopes NW.; desc. 207 ft. over NE. slope.

37.00

A branch, 2 lks. wide, course NW.; asc. 45 ft. over SE. slope.

40.20


A spur, slopes W.; desc. 4 ft. over NW. slope.

40.42

Point for original $\frac{1}{4}$ sec. cor., determined by reference to the record bearing and distance from the original SE. bearing tree.

At point for corner,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A fir, 18 ins. diam., bears S.8°E., 34 lks. dist., with blaze healed. I re-blaze and re-mark this old bearing tree $\frac{1}{4}$ S 30 B T.

A fir, 18 ins. diam., bears N.81 $\frac{1}{2}$ °W., 44 lks. dist., mkd. $\frac{1}{4}$ S 25 B T. (New B.T.)

Thence

N. 0° 34' W., with new measurement.

Desc. 50 ft. over NW. slope.

11.10

A branch, 3 lks. wide, course NW.; asc. 20 ft. over SW. slope.

12.00

A spur, slopes W.; desc. 13 ft. over NW. slope.

13.10

A branch, 3 lks. wide, course W.; asc. 256 ft. over SW slope.

30.70


A spur, slopes SE.; asc. 143 ft. over SE. slope.

40.19

Point for original cor. of secs. 19, 24, 25, and 30, determined by reference to the record measurements from the original SW. and NW. bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 19, 24, 25, and 30, with brass cap mkd.



1943

from which

A white fir, 20 ins. diam., bears S.40°W., 45 lks. dist., with partial scribe marks on decayed face of