

Dependent Resurvey of the W. Bdy. of the T. 25 S., R. 3 W.

CHAINS

from which

A white oak, 22 ins. diam., bears N.10 3/4°E., 195 lks. dist., on which I uncovered the scribe marks 1/4 S on decayed old blaze. (Old B.T.)

A white oak, 40 ins. diam., dead and down, bears N.24°W., 176 lks. dist., with only evidence of ax marks on decayed old blaze. (Old B.T.)

A black oak, 15 ins. diam., bears N.18 3/4°E., 204 lks. dist., mkd. 1/4 S 7 B T. (New B.T.)

A white oak, 11 ins. diam., bears N.43°W., 269 lks. dist., mkd. 1/4 S 12 B T. (Old B.T.)

Thence

N. 0° 46' E., with new measurement.

Asc. 19 ft. over rolling SW. slope.

3.40 A spur, slopes W.; desc. 7 ft. over rolling NW. slope.

9.60 Dry bed of creek, 2 lks. wide, course SW.; asc. 250 ft. over broken SE. slope.

18.00 A shallow ravine, course SE.

26.00 Enter heavy timber and dense undergrowth, bears NW. and SE.

28.00 W. side of saddle of spur ridge, bears NW. and SE.; continue to ascend 67 ft. over SE. slope.


34.40 Leave heavy timber and dense undergrowth and enter old clearing, bears NW. and SE.

35.40 Top of ascent on E. slope; desc. 37 ft. over NE. slope.

40.67 A spring branch, 1 lk. wide, course NE., in head of ravine, course NE.; asc. 1 ft. over SE. slope.

40.70 Proportional measurement.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 1, 6, 7, and 12, with brass cap mkd.



from which

A fir, 5 ins. diam., bears N.64°E., 150 lks. dist., mkd. T 25 S R 3 W S 6 B T.

A fir, 5 ins. diam., bears S.6 1/2°W., 93 lks. dist., mkd. T 25 S R 4 W S 12 B T.

Dig pits, 18x18x12 ins., in each sec., 3 ft. dist.

From this point a spring bears S.40°W., 80 lks. dist., flows NE.

Land, mountainous, rolling, and level.
Soil, sandy loam and rocky clay; 2d and 3d rate.
Timber, fir, oak, cedar, alder, hemlock, and maple.
Undergrowth, vinemaple, salmonberry, salal, willow,