

Dependent Resurvey of the W. Bdy. of T. 25 S., R. 3 W.

CHAINS

arrowwood, poison oak, and bracken.

N. 0° 46' E., bet. secs. 1 and 6.

Asc. 8 ft. over SE. slope, through scattering timber and undergrowth in old clearing.

2.00 A spur, slopes NE.; desc. 395 ft. over broken NE. slope.


21.80 A branch, 6 lks. wide, course NW.; asc. 120 ft. over SW. slope.

24.30 A dim road, bears NW. and SE.

31.70 A spur, slopes W.; desc. 74 ft. over NW. slope.

40.70<sup>1</sup>/<sub>2</sub> Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor.; with brass cap mkd.



from which

A madrona, 7 ins. diam., bears S.44°E., 126 lks. dist., mkd. on bark  $\frac{1}{4}$  S 6 B T.

A fir, 5 ins. diam., bears S.41°W., 215 lks. dist., mkd.  $\frac{1}{4}$  S 1 B T.

Desc. 70 ft. over NW. slope.

54.00 Calapooya Creek, 60 lks. wide, course SW.; asc. 28 ft. over rolling bottom land to township corner.


70.40 Calapooya Creek, 60 lks. wide, course S.15°E.

71.35 A power line of California-Oregon Power Company, bears N.42°E. and S.42°W.

81.41 Point for original cor. of Tps. 24 and 25 S., Rs. 3 and 4 W., determined by reference to the record distances from the old SE., SW., and NW. bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, for cor. of Tps. 24 and 25 S., Rs. 3 and 4 W., with brass cap mkd.



from which

A badly decayed maple stump, 16 ins. diam., bears S.64°E., 93 lks. dist. on which no marks could be found. (Old B.T.)

The stumphole of a fir, bears S.72°W., 8 lks. dist., which is the remains of an old bearing tree.