

Dependent Resurvey of the W. Bdy. of T. 25 S., R. 3 W.

CHAINS

The fallen and badly decayed remains of a maple, 36 ins. diam., bears N.21°W., 20 lks. dist., with only ax marks remaining to identify this as an old bearing tree. Local settlers verify this as an old bearing tree on which they have seen the original inscription more than forty years ago.

A fir, 5 ins. diam., bears N.60½°E., 85 lks. dist., mkd. T 24 S R 3 W S 31 B T. (New B.T.)

A fir, 5 ins. diam., bears S.58°E., 109 lks. dist., mkd. T 25 S R 3 W S 6 B T. (New B.T.)

A fir, 50 ins. diam., bears S.69°W., 333 lks. dist., mkd. T 25 S R 4 W S 1 B T. (New B.T.)

An incense cedar, 14 ins. diam., bears N.45 3/4°W., 133 lks. dist., mkd. T 24 S R 4 W S 36 B T. (New B.T.)

Land, rolling and mountainous.  
Soil, sandy loam and rocky clay; 1st and 3d rate.  
Timber, fir, alder, maple, cedar, oak, and madrona.  
Undergrowth, vinemaple, willow, arrowwood, hazel, lilac, salmonberry, bracken, poison oak, and salal.

---

Dependent Resurvey of Part of the N.Bdy. of sec. 6,  
T. 25 S., R. 3 W.

---

"Reestablishment of the survey executed by John Littrell,  
Deputy Surveyor, in 1867."

From the cor. of Tps. 24 and 25 S., Rs. 3 and 4 W.,  
heretofore described

S. 88° 05' E., along the N. bdy. of sec. 6, in conflict  
with sec. 31, T. 24 S., R. 3 W.  
Over rolling bottom land, in old clearing.

3.00 Leave bottom land, bears N. and S.; asc. 113 ft. over  
rolling broken W. slope.

8.66 A power line of California-Oregon Power Company, bears  
N.42°E. and S.42°W.

9.90 A spur, slopes N.20°W.; enter heavy timber and dense  
undergrowth, bears N. and S.; desc. 110 ft. over NE.  
slope.

13.80 Calapooya Creek, 60 lks. wide, course NW.; asc. 20 ft.  
over gently rolling bottom land.

20.60 Calapooya Creek, 60 lks. wide, course S.20°W.; thence  
over almost level bottom land.

25.40 Leave bottom land, bears NE. and SW.; asc. 106 ft. over  
NW. slope.

30.50 A spur, slopes N.; desc. 15 ft. over NE. slope.

31.50 A ravine, course N.30°W.; asc. 147 ft. over NW. slope.

38.72 Point for original ¼ sec. cor. of sec. 6 only, determined  
at the record bearing and distance from the old SE.  
bearing tree.

At point for corner,