

Dependent Resurvey of the S. Bdy. of T. 24 S., R. 3 W.

CHAINS

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 31 only, with brass cap mkd.

$\frac{1}{4}$  S31

1944

from which

A cedar stump, 36 ins. diam., bears N.50°E., (not S.50°E.) 22 lks. dist., mkd. B T. (Old B.T.)

A fir, 15 ins. diam., bears S.40°E., (not N.50°W.) 56 lks. dist., with the inscription  $\frac{1}{4}$  S B T on old blaze which I efface. (Old B.T.)

A red cedar, 8 ins. diam., bears N.39°E., 20 lks. dist., mkd.  $\frac{1}{4}$  S 31 B T. (New B.T.)

A fir, 7 ins. diam., bears N.71°W., 151 lks. dist., mkd.  $\frac{1}{4}$  S 31 B T. (New B.T.)

From this point the  $\frac{1}{4}$  sec. cor. of sec. 6 only, on the N. bdy. of T. 25 S., R. 3 W., bears N.82°00'W., 1.09 chs. dist., heretofore described.

Thence

S. 89° 34' E., bet. secs. 6 and 31, with new measurement.

Desc. 75 ft. over NE. slope.

3.90 A branch, 1 lk. wide, course N.20°W.; asc. 268 ft. over NW. slope.

12.90 A spur, slopes N.20°W.; desc. 7 ft. over NE. slope.

14.80 A ravine, course N.20°W.; asc. 61 ft. over NW. slope.

17.40 A spur, slopes N.10°W.; desc. 4 ft. over NE. slope.

18.90 A ravine, course N.; asc. 79 ft. over NW. slope.

22.50 A spur, slopes N.; desc. 295 ft. over NE. slope.

39.09 The original cor. of secs. 5, 6, 31, and 32, the locus of which has been perpetuated by the county surveyor's iron pipe, 3 ft. long, 1 in. diam., firmly set in a small mound of stone.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with county surveyor's iron pipe deposited at the base, for cor. of secs. 5, 6, 31, and 32, with brass cap mkd.

T24S R3W

S31 | S32

S6 | S5

T25S

1944

from which

A hemlock, 12 ins. diam., dead and down, bears S.70°E., 8 lks. dist., with no marks remaining on decayed face of old blaze. (Old B.T.)

A hemlock, 12 ins. diam., dead and down, bears N.52°W., 10 lks. dist., with no marks remaining on