

Dependent Resurvey of the S° Bdy. of T. 24 S., R. 3 W.

CHAINS

from which

A fir, 30 ins. diam., dead and down, bears N.28°W., 12 lks. dist., with old surface scar visible on under side of tree. (Old B.T.)

A fir, 40 ins. diam., bears N.40½°E., 140 lks. dist., a county surveyor's bearing tree which I re-blaze and re-mark, over old surface scar, ¼ S 32 B T.

A fir, 30 ins. diam., bears S.2°W., 20 lks. dist., a county surveyor's bearing tree which I re-blaze and re-mark, over old surface scar, ¼ S 5 B T.

Thence

N. 89° 32' E., with new measurement.

Desc. 4 ft. over SE. slope, along N. side of logged over area.

0.40 A ravine, course S.; asc. 30 ft. over SW. slope.

2.50 A spur, slopes S.; desc. 15 ft. over SE. slope.

5.10 A branch, 1 lk. wide, course S.80°W.; asc. 322 ft. over broken SW. slope.

18.60 A spur, slopes S.; desc. 28 ft. over SE. slope.

22.15 A ravine, course S.; asc. 120 ft. over SW. slope.

28.90 A spur, slopes S.; desc. 63 ft. over SE. slope.

31.60 A ravine, course S.; asc. 62 ft. over SW. slope.

34.10 A spur, slopes S.; desc. 103 ft. over SE. slope.

39.86 The original cor. of secs. 4, 5, 32, and 33, the locus of which has been perpetuated by the county surveyor's fir stake, 4 ft. long, 4 ins. square, firmly set, mkd. S 33 on NE., S 4 on SE., S 5 on SW., and S 32 on NW. face.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the county surveyor's marked stake deposited at the base, for cor. of secs. 4, 5, 32, and 33, with brass cap mkd.

T24S R3W
S32 | S33
 S5 | S4
 T25S
 1944

from which

A cedar, 38 ins. diam., bears S.72°E., 13 lks. dist., with blaze healed. (Old B.T.)

A fir, 30 ins. diam., bears N.70½°W., 21 lks. dist., with blaze healed. (Old B.T.)

A cedar, 42 ins. diam., bears N.10½°E., 44 lks. dist., mkd. S 33 T 24 S R 3 WCS B T. (County surveyor's bearing tree.)

A hemlock, 24 ins. diam., bears S.61°W., 30 lks. dist., mkd. S 5 T 25 S R 3 W C S B T. (County surveyor's bearing tree.)