

Dependent Resurvey of the S: Bdy. of T. 24 S., R. 3 W.

CHAINS

from which

A fir, 60 ins. diam., bears N.33 $\frac{1}{4}$ °E., 79 lks.
dist., mkd. T 24 S R 3 W S 35 B T.

A red cedar, 12 ins. diam., bears S.29°E., 7 lks.
dist., mkd. T 25 S R 3 W S 2 B T.

A fir, 6 ins. diam., bears S.48 $\frac{1}{2}$ °W., 61 lks.
dist., mkd. T 25 S R 3 W S 3 B T.

A red cedar, 8 ins. diam., bears N.51 $\frac{1}{2}$ °W., 57 lks.
dist., mkd. T 24 S R 3 W S 34 B T.

Land, mountainous.

Soil, sandy loam and rocky clay; 2d and 3d rate.

Timber, fir, hemlock, cedar, alder, maple, chinquapin,
madrona, oak, and dogwood.

Undergrowth, vinemaple, salal, bracken, willow, arrowwood,
hazel, lilac, manzanita, slickleaf, salmonberry, syringa,
poison oak, and Oregon grape.

N.88° 26' E., bet. secs. 2 and 35.

Asc. 35 ft. over SW. slope, through heavy timber and
dense undergrowth.

1.80 A spur, slopes S.; desc. 15 ft. over SE. slope.

7.10 A branch, 1 lk. wide, course S.; asc. 115 ft. over SW.
slope.

14.70 A spur, slopes S.; desc. 212 ft. over SE. slope changing
to E. slope.

31.80 A branch, 4 lks. wide, course S.20°E.; asc. 23 ft. over
SW. slope.

32.70 A spur, slopes S.; desc. 37 ft. over SE. slope.

35.10 A branch, 4 lks. wide, course S.5°W.; asc. 132 ft. over
SW. slope.

39.40 Center line of a logging road under construction, bears
N. and S.

40.28 Point for original $\frac{1}{4}$ sec. cor., determined at record
bearing and distance from old SW. bearing tree.

At point for corner,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ $\frac{S35}{S2}$
1944

from which

A fir, 44 ins. diam., bears S.5°W., 52 lks. dist., mkd.
on bark $\frac{1}{4}$ S B T. I re-blaze and re-mark this old
bearing tree $\frac{1}{4}$ S 2 B T.

A hemlock, 6 ins. diam., bears N.16°W., 46 lks. dist.,
mkd. $\frac{1}{4}$ S 35 B T. (New B.T.)

Thence

S. 89° 40' E., with new measurement.