

11540 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Subdivision of T. 25 S., R. 3 W.

CHAINS

"Reestablishment of the survey executed by Laban H. Wheeler, Deputy Surveyor, in 1883."

I commence the dependent resurvey of the subdivision at the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp.

Thence

N. 1° 59' E., bet. secs. 35 and 36.

Asc. 138 ft. over S. slope, changing to SE. slope, through heavy timber and dense undergrowth.


10.70 A spur, slopes SE.; desc. 36 ft. over rolling broken NE. slope.

17.70 Foot of descent on E. slope.; asc. 20 ft. over rolling broken SE. slope.

26.70 A spur, slopes E.; desc. 39 ft. over rolling NE. slope.

31.53 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



from which

A sugar pine, 30 ins. diam., bears S.  $18\frac{1}{2}^\circ$  E., 18 lks. dist., mkd.  $\frac{1}{4}$  S 36 B T.

An incense cedar, 48 ins. diam., bears N.  $88\frac{1}{2}^\circ$  W., 11 lks. dist., mkd.  $\frac{1}{4}$  S 35 B T.


Desc. 163 ft. over rolling broken NE. slope.

54.15 A branch, 8 lks. wide, course E.; asc. 69 ft. over SE. slope.

60.30 A spur, slopes E.; desc. 48 ft. over NE. slope.

63.06 Proportional measurement.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 25, 26, 35, and 36, with brass cap mkd.



from which

A fir, 28 ins. diam., bears N.  $14\frac{1}{4}^\circ$  E., 66 lks. dist., mkd. T 25 S R 3 W S 25 B T.

A fir, 16 ins. diam., bears S.  $26\frac{3}{4}^\circ$  E., 55 lks. dist., mkd. T 25 S R 3 W S 36 B T.

A fir, 22 ins. diam., bears S.  $71\frac{3}{4}^\circ$  W., 41 lks. dist., mkd. T 25 S R 3 W S 35 B T.