

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with decayed remains of squared stake deposited at the base, for cor. of secs. 23, 24, 25, and 26, with brass cap mkd.

T25S R3W	
S23	S24
S26	S25
1943	

from which

A fir, 36 ins. diam., bears N.11½°E., 34 lks. dist., with blaze healed. (Old B.T.)

A fir, 38 ins. diam., bears S.42°E., 80 lks. dist., with blaze healed. (Old B.T.)

A yew, 12 ins. diam., bears S.45°W., 10 lks. dist., with partial scribe marks on badly weathered face of old blaze. (Old B.T.)

A hemlock, 30 ins. diam., bears N.25°W., 62 lks. dist., with partial scribe marks visible on incompletely healed old blaze. (Old B.T.)

A fir, 36 ins. diam., bears S.51¼°W., 72 lks. dist., mkd. T 25 S R 3 W S 26 B T. (New B.T.)

Land, mountainous and rolling mountainous.  
 Soil, sandy loam and rocky clay; 2d and 3d rate.  
 Timber, fir, hemlock, pine, cedar, yew, alder, maple, madrona, dogwood, chinquapin, and oak.  
 Undergrowth, vinemaple, rhododendron, salal, arrowwood, willow, lilac, huckleberry, bracken, salmonberry, hazel, manzanita, and slickleaf.

From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp.

S. 72° 46' W., bet. secs. 24 and 25.

- 4.00 Asc. 66 ft. over SE. slope, changing to E. slope, through heavy timber and dense undergrowth.  
A spur, slopes SE.; asc. 34 ft. over rolling broken SE. slope.
- 13.10 A spur, slopes S.; desc. 420 ft. over SW. slope, changing to precipitous W. slope.
- 19.40 Top of bluff, 75 ft. high, bears N. and S.
- 25.20 A branch, 1 lk. wide, course SW.; desc. 74 ft. over broken SW. slope.
- 33.80 Center of a swampy spring hole, 60 lks. in diameter, drains SE.; asc. 20 ft. over SE. slope.
- 39.50 A spur, slopes S.20°E.; desc. 6 ft. over SW. slope.
- 40.40 A branch, 1 lk. wide, course S.20°E.; asc. 55 ft. over SE. slope.
- 43.77 Proportional measurement.