


Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS



From which

A fir, 60 ins. diam., bears N.20°E., 27 lks. dist., on which I uncovered the scribe marks  $\frac{1}{4}$  S B T beneath 60 years overgrowth. I added the marks 24 to the inscription on this old bearing tree.

A fir, 36 ins. diam., bears S.65°W., 74 lks. dist., on which I uncovered the scribe marks  $\frac{1}{4}$  S B T beneath 60 years overgrowth. I added the marks 23 to the inscription on this old bearing tree.

The old blazed line passes directly through this corner point.

Thence

N. 0° 28' E., with new measurement.

Asc. 41 ft. over SW. slope.


3.00 A spur, slopes SE.; asc. 312 ft. over broken SE. slope.

22.60 A branch, 2 lks. wide, course S.85°E.

46.66 Point for original cor. of secs. 13, 14, 23, and 24, determined by reference to the record measurements from all of the old bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 13, 14, 23, and 24, with brass cap mkd.



from which

A decayed hemlock stub, 48 ins. diam., bears N.42 $\frac{1}{2}$ °E., 18 lks. dist., on which the scribe marks B T remain. (Old B.T.)

A fir, 24 ins. diam., bears S.11 $\frac{1}{2}$ °E., 45 lks. dist., on which I uncovered the scribe marks S 24 T 25 R 3 B T beneath 60 years overgrowth. (Old B.T.)

A fir, 48 ins. diam., bears S.46 $\frac{1}{2}$ °W., 33 lks. dist., with partial scribe marks on charred face of old blaze. I re-blaze and re-mark this old bearing tree T 25 S R 3 W S 23 B T.

A fir, 20 ins. diam., bears N.78°W., 37 lks. dist., on which I uncovered the scribe marks S 14 T 25 R 3 B T beneath 60 years overgrowth. I changed the marks S 14 to S 23 on this old bearing tree.

A fir, 40 ins. diam., bears N.12 $\frac{1}{2}$ °E., 73 lks. dist., mkd. T 25 S R 3 W S 13 B T. (New B.T.)

A fir, 40 ins. diam., bears N.37 $\frac{1}{2}$ °W., 53 lks.