

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS

N. 0° 12' W., bet. secs. 13 and 14.

Asc. 826 ft. over broken S. slope, through heavy timber and dense undergrowth.

5.90 A branch, 3 lks. wide, course SE.

12.80 A branch, 2 lks. wide, course SE.


21.80 A branch, 1 lk. wide, course SE.

30.50 Top of a sloping bluff, 70 ft. high, bears N.85°W. and S.85°E.

45.12 Point for original $\frac{1}{4}$ sec. cor., determined by reference to the record measurements from both old bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A dead hemlock, 22 ins. diam., bears N.76 $\frac{1}{2}$ °E., 31 lks. dist., mkd. $\frac{1}{4}$ S B T. (Old B.T.)

A hemlock, 11 ins. diam., bears S.83°W., 12 lks. dist., mkd. $\frac{1}{4}$ S B T. (Old B.T.)

A fir, 36 ins. diam., bears S.59°E., 56 lks. dist., mkd. $\frac{1}{4}$ S 13 B T. (New B.T.)

A fir, 48 ins. diam., bears N.77°W., 25 lks. dist., mkd. $\frac{1}{4}$ S 14 B T. (New B.T.)

Thence

N. 0° 47' E., with new measurement.

Asc. 158 ft. over S. slope, changing to SW. slope.

10.65 A ridge, bears N.85°E. and S.85°W.; a trail and telephone line, bears E. and W.; desc. 178 ft. over NW. slope.

18.60 A branch, 1 lk. wide, course W.; asc. 150 ft. over SW. slope.

36.40 A spur, slopes NW.; desc. 359 ft. over precipitous broken N. slope.

42.20 Top of bluff, 80 ft. high, bears E. and W.

45.02 Point for original cor. of secs. 11, 12, 13, and 14, determined by reference to the record measurements from all of the old bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 11, 12, 13, and 14, with brass cap mkd.