

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS	
	A fir, 42 ins. diam., bears S.14°W., 80 lks. dist., mkd. $\frac{1}{4}$ S 13 B T.
	Asc. 120 ft. over SE. slope.
53.50	A trail and telephone line on top of a ridge, bears NE. and SW.; desc. 246 ft. over precipitous NW. slope.
67.50	A ravine, course NW.; asc. 15 ft. over NE. slope.
70.50	A spur, slopes NW.; desc. 345 ft. over NW. slope, changing to W. slope.
78.90	A ravine, course NW.; desc. 57 ft. over broken N. slope.
91.08	The cor. of secs. 11, 12, 13, and 14.
	Land, mountainous. Soil, sandy loam and rocky clay; 2d, 3d, and 4th rate. Timber, fir, hemlock, cedar, yew, pine, chinquapin, maple, madrona, alder, and dogwood. Undergrowth, vinemaple, rhododendron, manzanita, willow, slickleaf, bracken, arrowwood, hazel, and salal.
	<hr/>
	N. 0° 39' E., bet. secs. 11 and 12.
	Desc. 457 ft. over steep broken N. slope, through heavy timber and dense undergrowth.
9.00	A branch, 2 lks. wide, course NW.; asc. 59 ft. over SW. slope.
13.00	A spur, slopes NW.; desc. 265 ft. over NW. slope, changing to N. slope.
17.50	A graded and graveled logging road, bears E. and W.
20.50	Dry bed of creek, 10 lks. wide, course N.85°W.; asc. 86 ft. over S. slope, changing to SW. slope.
24.60	Same logging road, bears NW. and SE.
25.60	W. edge of swamp, 1.50 rchs. in diameter; thence over level land.
26.70	Leave level land, bears E. and W.; asc. 100 ft. over S. slope.
38.40	A spur, slopes W.; desc. 67 ft. over NW. slope, changing to N. slope.
39.30	Same logging road, bears NE. and SW.
45.80	Point for original $\frac{1}{4}$ sec. cor., determined by reference to the record measurements from both old bearing trees.
	At point for corner,
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	from which
	A hemlock, 7 ins. diam., bears S.75 3/4°E., 13 lks.