

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp.

N. 2° 10' E., bet. secs. 34 and 35.

Asc. 241 ft. over SE. slope, through heavy timber and dense undergrowth.

17.40 A spur, slopes SE.; thence over E. slope.

19.00 Head of ravine, course SE.; asc. 62 ft. over SE. slope.

26.10 A spur, slopes S.80°E.; desc. 118 ft. over NE. slope.


29.50 Top of bluff, 392 ft. high, bears N.70°W. and S.70°E.

30.50 Foot of bluff; thence over broken E. slope.

46.38 Point for original $\frac{1}{4}$ sec. cor., determined at the record bearing and distance from the original NE. bearing tree.

At point for corner,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A red cedar, 14 ins. diam., bears N.62°E., 22 lks. dist., with only ax marks remaining on decayed face of old blaze. (Old B.T.)

A fir, 11 ins. diam., bears S.35°E., 5 lks. dist., mkd. $\frac{1}{4}$ S 35 B T. (New B.T.)

A fir, 22 ins. diam., bears S.88°W., 36 lks. dist., mkd. $\frac{1}{4}$ S 34 B T. (New B.T.)

Thence

N. 0° 11' E., with new measurement.

Desc. 11 ft. over broken E. slope.

5.80 A shallow ravine, course E.

12.20 A shallow ravine, course E.

17.10 A branch, 5 lks. wide, course E.; asc. 95 ft. over SE. slope.

28.30 A spur, slopes E.; desc. 49 ft. over NE. slope.

33.10 A branch, 5 lks. wide, course E.; asc. 78 ft. over SE. slope.

40.54 Point for original cor. of secs. 26, 27, 34, and 35, determined by reference to the record measurements from all of the original bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 26, 27, 34, and 35, with brass cap mkd.