

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS

- 77.98 The cor. of secs. 22, 23, 26, and 27.  
 Land, mountainous.  
 Soil, sandy loam and rocky clay; 2d and 3d rate.  
 Timber, fir, hemlock, pine, cedar, yew, alder, chinquapin, maple, and madrona; undergrowth, vinemaple, salal, hazel, arrowwood, willow, bracken, manzanita, and slickleaf.
- 
- N. 6° 33' E., bet. secs. 22 and 23.  
 Desc. 103 ft. over NE. slope. through heavy timber and dense undergrowth.
- 4.75 A branch, 10 lks. wide, course E.; asc. 17 ft. over broken SE. slope.
- 9.05 A branch, 6 lks. wide, course SE.; asc. 79 ft. over SW. slope, changing to S. slope.
- 18.60 A spur, slopes SE.; desc. 25 ft. over NE. slope.
- 24.20 A branch, 2 lks. wide, course SE.; asc. 199 ft. over SW. slope, changing to SE. slope.
- 44.00 A spur, slopes SE.; desc. 26 ft. over NE. slope.
- 47.60 A branch, 2 lks. wide, course SE.; asc. 35 ft. over SW. slope.
- 50.00 Proportional measurement.  
 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
- S22 | S23  
 1943
- from which
- A fir, 36 ins. diam., bears S. 64 $\frac{1}{2}$ ° E., 18 lks. dist., mkd.  $\frac{1}{4}$  S 23 B T.
- A fir, 44 ins. diam., bears S. 86° W., 41 lks. dist., mkd.  $\frac{1}{4}$  S 22 B T.
- Asc. 216 ft. over SW. slope, changing to S. slope.
- 69.00 A spur, slopes SE.; desc. 29 ft. over NE. slope.
- 73.55 A branch, 2 lks. wide, course SE.; asc. 322 ft. over SW. slope, changing to SE. slope.
- 75.55 A graded and graveled logging road, bears E. and W.
- 92.00 A trail and telephone line on top of a ridge, bears N. 70° E. and S. 70° W.; desc. 173 ft. over NW. slope.
- 100.00 Point for original cor. of secs. 14, 15, 22, and 23, determined at record distances from all old bearing trees.  
 At point for corner,  
 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 14, 15, 22, and 23, with brass cap mkd.