


Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS



from which
A fir, 60 ins. diam., bears S.48°W., 8 lks. dist.,
mkd. on bark $\frac{1}{4}$ S B T. I re-blaze and re-mark this
old bearing tree $\frac{1}{4}$ S 11 B T.

A hemlock, 30 ins. diam., bears N.37°W., 20 lks. dist.,
with no marks remaining on face of old blaze which
has been mutilated about 20 years ago. (Old B.T.)

A fir, 42 ins. diam., bears S.35°W., 52 lks. dist.,
mkd. $\frac{1}{4}$ S 10 B T. (New B.T.)

Thence

N. 0° 31' E., with new measurement.

Asc. 30 ft. over S. slope, changing to SW. slope.

6.00 A spur, slopes W.; desc. 390 ft. over broken NW. slope.

7.50 A graded and graveled logging road, bears E. and W.

12.30 A spring branch, 1 lk. wide, course NW.

25.00 A spring branch, 1 lk. wide, course NW.


29.30 A branch, 4 lks. wide, course W.; asc. 207 ft. over SW. slope.

38.50 A spur, slopes W.; desc. 104 ft. over NW. slope.

41.66 Point for original cor. of secs. 2, 3, 10, and 11, deter-
mined at record measurements from old NE. and SW. bear-
ing trees.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the
ground, for cor. of secs. 2, 3, 10, and 11, with brass
cap mkd.



from which

A fir, 36 ins. diam., bears N.55°E., 20 lks. dist.,
with partial scribe marks on old bark blaze. I re-
blaze and re-mark this old bearing tree T 25 S R 3 W
S 2 B T.

A fir, 48 ins. diam., bears S.51°W., 12 lks. dist.,
with only ax marks on charred bark blaze. I re-
blaze and re-mark this old bearing tree T 25 S R 3 W
S 10 B T.

A fir, 10 ins. diam., bears S.40°E., 36 lks. dist.,
mkd. T 25 S R 3 W S 11 B T. (New B.T.)

A fir, 8 ins. diam., bears N.38°W., 30 lks. dist.,
mkd. T 25 S R 3 W S 3 B T. (New B.T.)

Land, mountainous,

Soil, sandy loam and rocky clay; 2d and 3d rate.

Timber, fir, hemlock, cedar, yew, alder, maple, and oak.

Undergrowth, vinemaple, salmonberry, bracken, and hazel.

From the cor. of secs. 1, 2, 11, and 12

N. 59° 53' W., bet. secs. 2 and 11.