

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS

looks at the decayed NW. side of this old bearing tree.

An incense cedar, 14 ins. diam., bears N.87½°E., 42 lks. dist., mkd. ¼ S 34 B T. (New B.T.)

A fir, 20 ins. diam., bears S.86¼°W., 37 lks. dist., mkd. ¼ S 33 B T. (New B.T.)

Thence

N. 1° 40' W., with new measurement.

Asc. 243 ft. over SW. slope, changing to broken SE. slope.

0.07 A spring branch, 1 lks. wide, course SW.

26.00 A flat topped spur ridge, bears NW. and SE.; continue to ascend 153 ft. over broken SE. slope.

39.56 Point for original cor. of secs. 27, 28, 33, and 34, determined by reference to the record measurements from the old NE., SE., and SW. bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28ins. in the ground, for cor. of secs. 27, 28, 33, and 34, with brass cap mkd.

T25S R3W	
S28	S27
S33	S34
1943	

from which

A chinquapin, 8 ins. diam., dead and down, bears N.62°E., 33 lks. dist., with partial scribe marks on decayed face of old blaze. (Old B.T.)

A chinquapin, 8 ins. diam., dead and down, bears S.84°E., 20 lks. dist., with partial scribe marks on decayed face of old blaze. (Old B.T.)

A chinquapin, 8 ins. diam., dead and down, bears S.56°W., 14 lks. dist., with partial scribe marks on decayed face of old blaze. (Old B.T.)

A fir, 20 ins. diam., bears N.32°E., 94 lks. dist., mkd. T 25 S R 3 W S 27 B T. (New B.T.)

A fir, 36 ins. diam., bears S.61 3/4°E., 76 lks. dist., mkd. T 25 S R 3 W S 34 B T. (New B.T.)

A fir, 20 ins. diam., bears S.84°W., 28 lks. dist., mkd. T 25 S R 3 W S 33 B T. (New B.T.)

A fir, 26 ins. diam., bears N.31°W., 36 lks. dist., mkd. T 25 S R 3 W S 28 B T. (New B.T.)

Land, mountainous.

Soil, sandy loam and rocky clay; 2d and 3d rate.

Timber, fir, hemlock, cedar, pine, yew, chinquapin, maple, madrona, alder, oak, and dogwood.

Undergrowth, vinemaple, salal, arrowwood, willow, bracken, hazel, manzanita, and slickleaf.

From the cor. of secs. 26, 27, 34, and 35

S. 84° 22' W., bet. secs. 27 and 34.