

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.


CHAINS

Asc. 387 ft. over broken E. slope, through heavy timber and dense undergrowth.

3.00 A spring branch, 3 lks. wide, course S.15°E.

40.93 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A fir, 40 ins. diam., bears N.7°E., 43 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.

A fir, 48 ins. diam., bears S.64°E., 16 lks. dist., mkd. $\frac{1}{4}$ S 34 B T.

Asc. 407 ft. over broken E. slope.

74.60 A rocky spur, slopes SE.; desc. 15 ft. over broken S. slope.

81.86 The cor. of secs. 27, 28, 33, and 34.

Land, mountainous.
Soil, sandy loam and rocky clay; 2d and 3d rate.
Timber, fir, hemlock, pine, cedar, alder, maple, yew, chinquapin, madrona, oak, and dogwood.
Undergrowth, vinemaple, salal, salmonberry, manzanita, slickleaf, bracken, hazel, willow, and arrowwood.

N. 5° 57' W., bet. secs. 27 and 28.


Asc. 151 ft. over broken S. slope, through heavy timber and dense undergrowth.

6.10 A spur, slopes SE.; desc. 99 ft. over NE. slope, changing to broken E. slope.

45.55 A branch, 1 lk. wide, course E.; asc. 55 ft. over SE. slope.

48.52 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A fir, 48 ins. diam., bears S.42°E., 64 lks. dist., mkd. $\frac{1}{4}$ S 27 B T.

A fir, 42 ins. diam., bears S.44°W., 59 lks. dist., mkd. $\frac{1}{4}$ S 28 B T.

Asc. 73 ft. over SE. slope, changing to broken E. slope.

70.80 A spring branch, 2 lks. wide, course E.