


# 11568 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS



from which

A fir, 32 ins. diam., bears N.59°E., 47 lks.  
dist., mkd.  $\frac{1}{4}$  S 22 B T.


A hemlock, 14 ins. diam., bears N.5°W., 58 lks.  
dist., mkd.  $\frac{1}{4}$  S 21 B T.

Asc. 5 ft. over SW. slope.

- 53.60 Top of ascent on W. slope; desc. 63 ft. over NW. slope.
- 56.80 Enter swamp, bears NE. and SW.
- 59.70 A branch, 4 lks. wide, course W.
- 62.80 Leave swamp, bears E. and W.; asc. 69 ft. over SW. slope.
- 74.10 A spur, slopes W.; desc. 104 ft. over NW. slope, changing to NE. slope.
- 76.15 A graded and graveled logging road, bears E. and W.
- 76.40 A telephone line, bears E. and W.
- 88.60 A branch, 3 lks. wide, course N.30°W.; desc. 32 ft. over broken W. slope.
- 97.90 A spur, slopes W.; desc. 80 ft. over NW. slope.
- 103.64 Point for original cor. of secs. 15, 16, 21, and 22, determined by reference to the record bearing and distance from the original SE. bearing tree.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 15, 16, 21, and 22, with brass cap mkd.



from which

A fir, 16 ins. diam., bears S.43°E., 74 lks. dist., on which I uncovered the scribe marks T 25 3 W S 22 B T beneath 60 years overgrowth. (Old B.T.)

A fir, 14 ins. diam., bears N.30°E., 22 lks. dist., mkd. T 25 S R 3 W S 15 B T. (New B.T.)

A fir, 16 ins. diam., bears S.12°E., 20 lks. dist., mkd. T 25 S R 3 W S 22 B T. (New B.T.)

A fir, 18 ins. diam., bears S.61 $\frac{1}{4}$ °W., 38 lks. dist., mkd. T 25 S R 3 W S 21 B T. (New B.T.)

A fir, 20 ins. diam., bears N.32 $\frac{1}{2}$ °W., 6 lks. dist., mkd. T 25 S R 3 W S 16 B T. (New B.T.)

Land, mountainous and level.  
Soil, sandy loam and rocky clay; 1st, 2d, and 3d rate.  
Timber, fir, hemlock, cedar, alder, yew, maple, dogwood,