

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS	
	<p>chinquapin, and pine. Undergrowth, vinemaple, willow, arrowwood, manzanita, slickleaf, bracken, salmonberry, hardhack, ninebark, hazel, rhododendron, and syringa.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23 S. 89° 56' W., bet. secs. 15 and 22. Desc. 73 ft. over broken NW. slope, through heavy timber and dense undergrowth.</p>
14.60	A branch, 4 lks. wide, course N.; asc. 51 ft. over NE. slope.
21.60	A spur, slopes N.; desc. 284 ft. over broken NW. slope.
31.30	A spring branch, 2 lks. wide, course N.15°W.
43.10	Point for original $\frac{1}{4}$ sec. cor.; determined by reference to the record measurements from both original bearing trees. At point for corner, Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S15}{S22}$ <p>1943</p>
	from which
	<p>A hemlock, 25 ins. diam., bears N.29°E., 15 lks. dist., with blaze healed. (Old B.T.)</p> <p>A hemlock, 18 ins. diam., bears S.55°W., 23 lks. dist., with blaze healed. (Old B.T.)</p> <p>A fir, 20 ins. diam., bears S.59 3/4°E., 29 lks. dist., mkd. $\frac{1}{4}$ S 22 B T. (New B.T.)</p>
	Thence
	N. 86° 34' W., with new measurement.
	Desc. 35 ft. over NW. slope.
1.00	A branch, 3 lks. wide, course N.15°W.; asc. 10 ft. over NE. slope.
5.00	A spur, slopes N.; desc. 53 ft. over NW. slope.
8.00	A graded logging road, bears N. and S.
8.50	A branch, 5 lks. wide, course N.20°W.; asc. 4 ft. over NE. slope.
10.20	A spur, slopes NW.; desc. 49 ft. over NW. slope.
14.00	A branch, 4 lks. wide, course N.; asc. 18 ft. over NE. slope.
16.00	A spur, slopes N.; desc. 69 ft. over NW. slope.
19.70	A branch, 2 lks. wide; course NW.; asc. 20 ft. over NE. slope.
23.00	A spur, slopes NW.; desc. 79 ft. over NW. slope.