

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS	<p>A fir, 16 ins. diam., bears N.8½°W., 110 lks. dist., mkd. ¼ S 9 B T. (New B.T.)</p> <p>Thence</p> <p>N. 0° 17' E., with new measurement.</p> <p>Desc. 14 ft. over N. slope, along top of spur.</p> <p>0.40 A graded and graveled logging road, and telephone line, bears NE. and SW.</p> <p>4.00 Leave spur, slopes N.15°W.; desc. 93 ft. over NE. slope.</p> <p>8.80 Same road and telephone line, bears E. and W. at sharp curve.</p> <p>15.90 Foot of descent on W. slope; asc. 16 ft. over SW. slope.</p> <p>18.90 A spur, slopes NW.; desc. 100 ft. over NE. slope.</p> <p>24.30 A branch, 20 lks. wide, course NW.; asc. 29 ft. over SW. slope.</p> <p>26.70 A spur, slopes NW.; desc. 122 ft. over broken NE. slope.</p> <p>38.90 A graded and graveled logging road, bears N.80°W. and S.80°E.</p> <p>43.20 The original cor. of secs. 3, 4, 9, and 10, the locus of which has been perpetuated by the county surveyor's hemlock stake, 3 ft. long, 4 ins. square, firmly set, mkd. S 3 on NE., S 10 C S on SE., S 9 on SW., and S 4 C S on NW. face.</p> <p>At point for corner,</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the county surveyor's marked stake deposited at the base, for cor. of secs. 3, 4, 9, and 10, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25S R3W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S4</td> <td style="padding: 0 5px;">S3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S9</td> <td style="padding: 0 5px;">S10</td> </tr> </table> <p>1943</p> </div> <p style="text-align: right;">from which</p> <p>A cedar stump, 50 ins. diam., bears N.55°E., 5 lks. dist., on which only ax marks remain. (Old B.T.)</p> <p>A fir, 62 ins. diam., bears N.35°E., 39 lks. dist., mkd. on bark T 25 S R 3 W S 3 C S B T. I re-blaze and re-mark this county surveyor's bearing tree T 25 S R 3 W S 3 B T.</p> <p>A maple, 7 ins. diam., bears S.41½°E., 35 lks. dist., mkd. S 10 T 25 R 3 W C S B T. (A county surveyor's B.T.)</p> <p>A fir, 8 ins. diam., bears S.58½°W., 36 lks. dist., mkd. S 9 T 25 R 3 W C S B T. (A county surveyor's B.T.)</p> <p>A hemlock, 6 ins. diam., bears N.51°W., 5 lks. dist., mkd. S 4 T 25 R 3 W C S B T. (A county surveyor's B.T.)</p> <p>A fir, 20 ins. diam., bears S.10 3/4°E., 131 lks. dist., mkd. T 25 S R 3 W S 10 B T. (New B.T.)</p> <p>Land, mountainous.</p>	S4	S3	S9	S10
S4	S3				
S9	S10				