

11578 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS
37.60


A branch, 4 lks. wide, course SW.

39.87

Point for original $\frac{1}{4}$ sec. cor., determined by reference to the record measurements from both original bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A fir, 48 ins. diam., bears S. $71\frac{1}{2}^{\circ}$ E., 38 lks. dist., mkd. on bark $\frac{1}{4}$ S B T. (Old B.T.)

A fir, 60 ins. diam., bears N. 54° W., 17 lks. dist., mkd. on bark $\frac{1}{4}$ S B T. (Old B.T.)

A fir, 22 ins. diam., bears S. $34\frac{1}{2}^{\circ}$ E., 45 lks. dist., mkd. $\frac{1}{4}$ S 28 B T. (New B.T.)

A fir, 32 ins. diam., bears S. 5° W., 63 lks. dist., mkd. $\frac{1}{4}$ S 29 B T. (New B.T.)

Thence

N. $3^{\circ} 16'$ E., with new measurement

Asc. 414 ft. over broken S. slope, changing to SW. slope.

7.60

A branch, 4 lks. wide, course SE.

29.60

A ridge, bears E. and W.; desc. 251 ft. over NW. slope.

54.10

A ravine, course W.; asc. 7 ft. over SW. slope.

56.70

A spur, slopes W.; desc. 38 ft. over NW. slope.

59.50


A branch, 1 lk. wide, course N. 80° W.; asc. 69 ft. over SW. slope, changing to W. slope.

71.24

Point for original cor. of secs. 20, 21, 28, and 29, determined at the mean position of the record measurements from the original NE., SE., and SW. bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 20, 21, 28, and 29, with brass cap mkd.



from which

A dead fir, 30 ins. diam., bears N. 44° E., 44 lks. dist., with partial scribe marks on old bark blaze. (Old B.T.)

A fir, 56 ins. diam., bears S. 44° E., 40 lks. dist., on which the old bark blaze has sloughed off and only faint ax marks were found. I re-blaze and re-mark this old bearing tree T 25 S R 3 W S 28 B T.