

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS

A fir, 32 ins. diam., bears S.45 3/4°W., 45 lks. dist., with partial scribe marks on old bark blaze. I re-blaze and re-mark this old bearing tree T 25 S R 3 W S 29 B T.

A red cedar, 12 ins. diam., bears N.11°E., 51 lks. dist., mkd. T 25 S R 3 W S 21 B T. (New B.T.)

A hemlock, 6 ins. diam., bears S.28°E., 17 lks. dist., mkd. T 25 S R 3 W S 28 B T. (New B.T.)

A red cedar, 16 ins. diam., bears S.27 1/4°W., 70 lks. dist., mkd. T 25 S R 3 W S 29 B T. (New B.T.)

A hemlock, 8 ins. diam., bears N.14°W., 18 lks. dist., mkd. T 25 S R 3 W S 20 B T. (New B.T.)

Land, mountainous.
Soil, sandy loam and rocky clay; 2d and 3d rate.
Timber, fir, hemlock, cedar, alder, yew, maple, pine, chinquapin, madrona, and dogwood.
Undergrowth, vinemaple, salal, salmonberry, willow, hazel, bracken, arrowwood, manzanita, and slickleaf.

From the cor. of secs. 21, 22, 27, and 28

S. 88° 42' W., bet. secs. 21 and 28.

Asc. 453 ft. over SE. slope, changing to precipitous E. slope, through heavy timber and dense undergrowth.

23.70 A trail and telephone line, bears NE. and SW.

26.90 A ridge, bears N.30°E. and S.30°W.; desc. 188 ft. over precipitous NW. slope.

30.00 Foot of descent on N. slope; asc. 88 ft. over precipitous broken N. slope.

38.34 Point for original 1/4 sec. cor., determined at the record bearing and distance from the original NE. bearing tree.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{S21}{S28}$$
 1943

from which

A fir, 40 ins. diam., bears N.50°E., 14 lks. dist., with partial scribe marks on old bark blaze. I re-blaze and re-mark this old bearing tree 1/4 S 21 B T.

A fir, 16 ins. diam., bears S.80°W., 49 lks. dist., mkd. 1/4 S 28 B T. (New B.T.)

Thence

N. 63° 11' W., with new measurement.

Desc. 563 ft. over precipitous NW. slope, changing to gentle NW. slope.

1.70 Top of bluff, 60 ft. high, bears NE. and SW.