

# 11580 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS	
26.85	A graded and graveled logging road, bears N. and S.
32.94	The cor. of secs. 20, 21, 28, and 29.
	Land, mountainous. Soil, sandy loam and rocky clay; 2d, 3d, and 4th rate. Timber, fir, hemlock, cedar, maple, alder, yew, madrona, chinquapin, pine, and dogwood. Undergrowth, vinemaple, salal, hazel, arrowwood, bracken, manzanita, slickleaf, willow, lilac, and syringa.
	<hr/>
	N. 0° 52' W., bet. secs. 20 and 21.
	Asc. 6 ft. over rolling broken W. slope, through heavy timber and dense undergrowth in partially logged area.
14.00	A flat topped spur, slopes N.15°W.; desc. 145 ft. over broken NE. slope.
31.30	A junction of graded and graveled logging roads, bearing E., W., and NW.
32.70	Same graded and graveled logging road, bears NE. and SW.
36.30	A spur, slopes NE.; desc. 74 ft. over NW. slope.
44.00	Foot of descent on W. slope near E. edge of small swamp.
44.18	Proportional measurement.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	from which
	A fir, 64 ins. diam., bears S.75 $\frac{1}{2}$ °E., 57 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.
	A fir, 40 ins. diam., bears N.53°W., 121 lks. dist., mkd. $\frac{1}{4}$ S 20 B T.
	Asc. 2 ft. over SW. slope.
48.00	Top of ascent on W. slope; desc. 474 ft. over broken NW. slope.
88.36	Point for original Cor. of secs. 16, 17, 20, and 21, determined at the record distance from each of the original bearing trees.
	At point for corner,
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 16, 17, 20, and 21, with brass cap mkd.
	from which
	A fir, 50 ins. diam., bears N.29°E., 35 lks. dist., mkd. on bark B T T 25 R 3 S 16. (Old B.T.)