

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS	
46.80	A graded and graveled logging road and telephone line, bears N. and S.
48.40	A branch, 2 lks. wide, course N.10°E.
61.00	Top of ascent on N. slope; desc. 20 ft. over NW. slope.
62.40	A branch, 3 lks. wide, course NE.; asc. 8 ft. over NE. slope.
63.40	Top of ascent on N. slope; desc. 23 ft. over NW. slope.
70.15	A branch, 3 lks. wide, course N.15°W.; enter heavy timber, bears N. and S.; asc. 73 ft. over NE. slope.
83.70	Top of ascent on N. slope; desc. 24 ft. over broken NW. slope.
86.86	The cor. of secs. 16, 17, 20, and 21.
	Land, mountainous and rolling. Soil, sandy loam and rocky clay; 1st, 2d, 3d rate. Timber, fir, hemlock, cedar, maple, chinquapin, alder, yew, madrona, and dogwood. Undergrowth, vinemaple, willow, bracken, hazel, salal, arrowwood, manzanita, slickleaf, salmonberry, and lilac.
	N. 1° 30' E., bet. secs. 16 and 17.
	Desc. 354 ft. over NW. slope, through heavy timber and dense undergrowth.
12.50	Enter a timbered swamp, bears E. and W.
15.00	Leave timbered swamp, bears E. and W.; asc. 21 ft. over SW. slope.
16.00	A spur, slopes W.; desc. 348 ft. over NW. slope.
33.00	A graded logging road, bears NE. and SW.
38.50	Proportional measurement.
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	from which
	A fir, 16 ins. diam., bears N.30°E., 56 lks. dist., mkd. $\frac{1}{4}$ S 16 B T.
	A fir, 22 ins. diam., bears N.15°W., 19 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.
	Desc. 50 ft. over NW. slope.
40.50	A branch, 3 lks. wide, course N.30°E.; asc. 6 ft. over SE slope.
44.40	A spur, slopes E.; desc. 73 ft. over NE. slope.
48.60	Same branch, 3 lks. wide, course NW.; asc. 39 ft. over SW. slope.