


Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS

bearing and distance from the old NE. bearing tree.

At point for corner,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A fir, 30 ins. diam., bears N.55°E., 21 lks. dist., with partial scribe marks visible in portion of old blaze which has been previously uncovered. The county surveyor re-blazed and re-marked this old bearing tree $\frac{1}{4}$ S 9 T 25 S R 3 W C S B T.

A maple, 12 ins. diam., bears S.74 $\frac{1}{2}$ °W., 50 lks. dist., mkd. $\frac{1}{4}$ S 8 T 25 S R 3 W C S B T. (A county surveyor's B.T.)

Thence


N. 1° 17' W., with new measurement.

Desc. 92 ft. over NW. slope.

- 7.10 A ravine, course N.80°W.; asc. 4 ft. over SW. slope.
- 8.60 A spur, slopes W.; desc. 62 ft. over NW. slope.
- 12.60 A ravine, course N.80°W.; asc. 35 ft. over SW. slope.
- 14.90 A spur, slopes N.80°W.; desc. 30 ft. over NW. slope.
- 17.60 A ravine, course N.80°W.; asc. 9 ft. over SW. slope.
- 19.80 A spur, slopes N.80°W.; desc. 63 ft. over NW. slope.
- 25.10 Dry bed of creek, 2 lks. wide, course NW.; asc. 50 ft. over SW. slope.
- 29.40 A spur, slopes W.; desc. 56 ft. over NW. slope.
- 34.60 A shallow ravine, course W.; asc. 23 ft. over SW. slope.
- 38.50 The original cor. of secs. 4, 5, 8, and 9, the locus of which has been perpetuated by the county surveyor's yew post, 4 ft. long, 4 ins. square, firmly set, mkd. T 25 S S 4 on NE., R 3 W S 9 on SE., S 8 on SW., and S 5 C S on NW. face.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with the county surveyor's marked stake deposited at the base, for cor. of secs. 5, 4, 8, and 9, with brass cap mkd.



from which

A cedar stump, 36 ins. diam., bears S.10°E.; 24 lks. dist., on which only ax marks remain. (Old B.T.)