

Dependent Resurvey of the Sub. of T. 25 S., R. 3 W.

CHAINS
19.70

A spur, slopes W.; desc. 52 ft. over NW. slope.

22.30

A ravine, course W.; asc. 433 ft. over SW. slope.

33.00

A spur, slopes W.; desc. 344 ft. over NW. slope.


40.20

A ravine, course N.85°W; asc. 39 ft. over SW. slope.

42.17

Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

A fir, 12 ins. diam., bears S.67°E., 49 lks. dist., mkd. $\frac{1}{4}$ S 8 B T.

A fir, 30 ins. diam., bears West, 44 lks. dist., mkd. $\frac{1}{4}$ S 7 B T.

Asc. 194 ft. over SW. slope.

47.50

A ridge, bears NW. and SE.; desc. 117 ft. over NE. slope.

57.40

A ravine, course E.; asc. 30 ft. over SE. slope.

62.20

A spur, slopes S.80°E.; desc. 186 ft. over NE. slope.

71.30


A ravine, course E.; asc. 263 ft. over SE. slope.

84.34

Point for original cor. of secs. 5, 6, 7, and 8, determined by reference to the record measurements from the old SE., SW., and NW. bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 5, 6, 7, and 8, with brass cap mkd.



from which

A fir, 40 ins. diam., bears S.40°E., 13 lks. dist., with blaze healed. I re-blaze and re-mark this old bearing tree T 25 S R 3 W S 8 B T.

A fir, 18 ins. diam., bears S.73 $\frac{1}{2}$ °W., 15 lks. dist., with blaze healed. (Old B.T.)

A fir, 18 ins. diam., bears N.18°W., 16 lks. dist., with partial scribe marks visible on portion of old blaze which has been previously uncovered. (Old B.T.)

A fir, 30 ins. diam., bears N.23 $\frac{3}{4}$ °E., 74 lks. dist., mkd. T 25 S R 3 W S 5 B T. (New B.T.)

Land, mountainous.

Soil, sandy loam and rocky clay; 2d and 3d rate.

Timber, fir, hemlock, cedar, alder, maple, chinquapin, yew, madrona, pine, and dogwood.