

11612

Retracement Portion West Bdy., T. 30 S., R. 7 W.

CHAINS

from which

A madrona, 10 ins. diam., bears N. 36° E., 34 lks. dist., mkd. T 30 S R 7 W S 31 BT. (Old B. T.)

A live oak, 8 ins. diam., bears S. 75° E., 41 lks. dist., mkd. T 31 S R 7 W S 6 BT. (Old B. T.)

A fir, 30 ins. diam., bears S. 78° W., 67 lks. dist., mkd. T 31 S R 8 W S 1 BT. (New B. T.)

A live oak, 7 ins. diam., bears N. 23° W., 33 lks. dist., mkd. T 30 S R 8 W S 36 BT. (New B. T.)

Thence

North, retracing the line bet. secs. 31 and 36.

Ascend S. slope, through heavy timber and dense undergrowth.

0.30 Foot of bluff, 30 ft. high.

3.00 Top of spur, slopes E.; descend NE. slope.


28.20 Creek, 1 lk. wide, course E.

30.10 Table Creek, 8 lks. wide, course S. 60° E.

36.90 Same creek, 8 lks. wide, course SW.

39.17 Fall 92 lks. E. of the 1/4 sec. cor., which is a stone, firmly set, mkd. and witnessed as described by the surveyor general. Alongside the old cor.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



from which

A yew, 16 ins. diam., bears S. 31° E., 50 lks. dist., mkd. 1/4 S 31 BT. (Old B. T.)

A maple, 6 ins. diam., bears N. 87°30' W., 34 lks. dist., mkd. 1/4 S 36 BT. (Old B. T.)

A fir, 10 ins. diam., bears S. 86°30' W., 35 lks. dist., mkd. 1/4 S 36 BT. (New B. T.)

The true course and length of this line is N. 1°21' W., 39.18 chs.

I continue my retracement North from the 1/4 sec. cor., counting distance from the Tp. cor.

41.00 Table Creek, 6 lks. wide, course SE.; ascend steep rocky S. slope.

50.45 Top of steep slope; thence along E. slope.

77.41 Fall 31 lks. W. of the old cor. of secs. 25, 30, 31 and 36, which is a stone, firmly set, mkd. and witnessed as described by the surveyor general, except that the NE. and SW. bearing trees have fallen. Alongside the old cor.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, with brass cap mkd.