

Retracement portion West Bdy., T. 30 S., R. 7 W.

CHAINS

T 30 S	
R 8 W	R 7 W
S 25	S 30
S 36	S 31
1918	

from which

A cedar, 16 ins. diam., bears N. 31°30' E., 55 lks. dist.,
mkd. T 30 S R 7 W S 30 BT. (New B. T.)

A fir, 36 ins. diam., bears S. 75° E., 42 lks. dist.,
mkd. T 30 S R 7 W S 31 BT. (Old B. T.)

A cedar, 8 ins. diam., bears S. 53° W., 50 lks. dist.,
mkd. T 30 S R 8 W S 36 BT. (New B. T.)

A cedar, 7 ins. diam., bears N. 70° W., 40 lks. dist.,
mkd. T 30 S R 8 W S 25 BT. (Old B. T.)

The true course and distance of this line from the $\frac{1}{4}$ sec. cor. is
N. 0°30' E., 38.24 chs.

Land, mountainous.

Soil, rocky granite loam, 3rd and 4th rate.

Timber, heavy fir, cedar, live oak, madrona and yew.

Undergrowth, dense arrowwood, fir, yew and live oak.

Retracement and Survey Portion South Bdy., T. 30 S., R. 7 W.

From the cor. of Tps. 30 and 31 S., Rs. 7 and 8 W.

East, retracing line bet. secs. 6 and 31.

Descend steep SE. slope.

- 2.15 Top of bluff, 150 ft. high.
- 5.25 Foot of bluff.
- 19.85 Top of spur, slopes SE.; descend.
- 21.90 Ravine, course S.; ascend.
- 23.20 Top of spur, slopes S.; descend.
- 24.75 Ravine, course S.; ascend.
- 25.75 Top of spur, slopes S.; descend.
- 31.65 Creek, 2 lks. wide, course NE.; ascend.
- 33.75 Top of spur, slopes NE.; descend.
- 36.15 Creek, 1 lk. wide, course N.; ascend.
- 36.90 Trail, bears N. and S.
- 38.10 Fall 61 lks. S. of the old $\frac{1}{4}$ sec. cor., located by reference to the bearing trees. At the exact corner point

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground,
for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 31	
$\frac{1}{4}$	S 6
1918	