

Retracement portion West Bdy., T. 31 S., R. 7 W.

CHAINS

Survey commenced March 13, 1918 and executed with a W. and L. E. Gurley solar compass, not numbered.

For description, test and approval of instrument and method of measurement, see Book "G" of this Group.

I commence at the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., the point for which is located by reference to the bearing trees, the NE. tree having fallen. At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 1, 6, 7 and 12, with brass cap mkd.

T 31 S	
R 8 W	R 7 W
S 1 S	6
S 12	S 7
1918	

from which

A fir, 8 ins. diam., bears N. 85° E., 43 lks. dist., mkd. T 31 S R 7 W S 6 BT. (New B. T.)

A fir, 10 ins. diam., bears S. 20° E., 50 lks. dist., mkd. T 31 S R 7 W S 7 BT. (Old B. T.)

A fir, 14 ins. diam., bears S. 46° W., 21 lks. dist., mkd. T 31 S R 8 W S 12 BT. (Old B. T.)

A fir, 16 ins. diam., bears N. 19° W., 26 lks. dist., mkd. T 31 S R 8 W S 1 BT. (Old B. T.)

Thence

North, retracing line bet. secs. 1 and 6.

Ascend SW. slope, through heavy timber and dense undergrowth.

- 9.80 Top of spur, slopes SW.; descend.
- 15.30 Ravine, course SW.; ascend.
- 21.60 Top of spur, slopes SW.; descend.
- 32.50 Rocky point, slopes W.
- 40.84 Fall 5 lks. E. of the point for old  $\frac{1}{4}$  sec. cor., located by reference to the bearing trees. The NW. tree fallen. At the exact cor. point

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$	
S 1	S 6
1918	

from which

A yellow pine, 50 ins. diam., bears S. 52° E., 39 lks. dist., mkd.  $\frac{1}{4}$  S 6 BT. (Old B. T.)

A fir, 40 ins. diam., bears N. 33° W., 49 lks. dist., mkd.  $\frac{1}{4}$  S 1 BT. (New B. T.)

The true course and length of this line is N. 0°04' W., 40.84 chs.

I continue my retracement North from the  $\frac{1}{4}$  sec. cor., counting distance from the sec. cor.