

Retracement Portion West Bdy., T. 31 S., R. 7 W.

CHAINS  
 41.40 Ravine, course W.; ascend.  
 48.60 Top of rocky point, slopes SW.; thence ascend along W. slope.  
 53.25 Summit of rocky ridge, bears NW. and SE.; descend.  
 56.55 Trail, bears NW. and SE.  
 62.30 Trail, bears NW. and SE.  
 67.20 Head of ravine, course S. 70° E.; ascend steep rocky SE. slope.  
 76.35 Top of rocky point, slopes SE.; descend.  
 79.05 Ravine, course SE.; ascend steep S. slope.  
 81.91 Fall 1 lk. E. of the cor. of Tps. 30 and 31 S., Rs. 7 and 8 W., heretofore described.

The true course and length of this line from the  $\frac{1}{4}$  sec. cor. is N. 0°01' W., 41.07 chs.

Land, mountainous.  
 Soil, red clay loam to 42.00 chs., 2nd rate; balance gravel and rocky loam, 4th rate.  
 Timber, fir, live oak, madrona and yellow pine.  
 Undergrowth, fir, arrowwood, chaparral and live oak.

Retracement Portion Subdivisions, T. 31 S., R. 7 W.

I commence at the cor. of secs. 3, 4, 9 and 10, the point for which is located by reference to the bearing trees. At the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 3, 4, 9 and 10, with brass cap mkd.

T 31 S	R 7 W
S 4	S 3
S 9	S 10
1918	

from which

A fir, 24 ins. diam., bears N. 77° E., 40 lks. dist., mkd. T 31 S R 7 W S 3 BT. (Old B. T.)

A white oak, 8 ins. diam., bears S. 57° E., 27 lks. dist., mkd. T 31 S R 7 W S 10 BT. (Old B. T.)

A black oak, 12 ins. diam., bears S. 33° W., 23 lks. dist., mkd. T 31 S R 7 W S 9 BT. (Old B. T.)

A fir, 20 ins. diam., bears N. 8° W., 29 lks. dist., mkd. T 31 S R 7 W S 4 BT. (Old B. T.)

Thence

North, retracing line bet. secs. 3 and 4.

Along gentle W. slope, through heavy timber and dense undergrowth.

1.70 Top of spur, slopes W.; descend.  
 6.95 Creek, 2 lks. wide, course W.; ascend.  
 13.80 Top of rocky spur, slopes W.; descend steep N. slope.  
 19.90 Ravine, course W.; ascend over conglomerate bedrock.