

Retracement Portion Subdivisions, T. 31 S., R. 7 W.

CHAINS

T 31 S	R 7 W
S 6	S 5
S 7	S 8
1918	

from which

A fir, 30 ins. diam., bears N. 31° E., 51 lks. dist., mkd. T 31 S R 7 W S 5 BT. (New B. T.)

A fir, 36 ins. diam., bears S. 72° E., 56 lks. dist., mkd. T 31 S R 7 W S 8 BT. (New B. T.)

A madrona, 16 ins. diam., bears S. 29° W., 33 lks. dist., mkd. T 31 S R 7 W S 7 BT. (Old B. T.)

A cedar, 16 ins. diam., bears N. 40° W., 50 lks. dist., mkd. T 31 S R 7 W S 6 BT. (Old B. T.)

The true course and length of this line from the 1/4 sec. cor. is S. 87°51' W., 37.96 chs.

Land, mountainous.

Soil, shale and granite loam, 3rd rate.

Timber, black oak, white oak, fir, madrona and live oak.

Undergrowth, live oak, arrowwood and fir.

S. 87°34' W., retracing line bet. secs. 6 and 7.

Ascend SE. slope, through heavy timber and dense undergrowth.

3.60 Top of spur, slopes SE.; descend.

16.50 Creek, 1 lk. wide, course SE.; ascend NE. slope.

23.60 Same creek, course NE.

37.30 Top of ridge, bears NW. and SE.; descend.

40.23 Fall 29 lks. N. of the 1/4 sec. cor., located by reference to the bearing trees. At the exact corner point

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

S 6
1/4 S 7
1918

from which

A live oak, 8 ins. diam., bears N. 80° E., 57 lks. dist., mkd. 1/4 S 6 BT. (New B. T.)

A live oak, 8 ins. diam., bears S. 28° W., 15 lks. dist., mkd. 1/4 S 7 BT. (Old B. T.)

The true course and length of this line is S. 87°09' W., 40.23 chs.

I continue my retracement S. 87°34' W. from the 1/4 sec. cor., counting distance from the sec. cor.

44.00 Mouth of tunnel; Purdum Mine; extends North, 100 ft.

46.25 Head of ravine, course S.; ascend.

50.15 Top of spur, slopes S.; descend.

50.75 Trail, bears N. and S.