

Retracement Portion Subdivisions, T. 31 S., R. 7 W.

CHAINS

- 53.15 Draw, course S.; ascend.
- 58.55 Top of spur, slopes SW.; descend.
- 68.15 Creek, 3 lks. wide, course S.; ascend.
- 73.25 Top of spur, slopes S.; descend.
- 77.34 Fall 127 lks. N. of the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., heretofore described.


The true course and length of this line from the $\frac{1}{4}$ sec. cor. is S. 85°36' W., 37.19 chs.

Land, mountainous.
Soil, rocky granite and red clay loam, 3rd and 4th rate.
Timber, live oak, fir, madrona and tan oak.
Undergrowth, live oak, arrowwood, fir and tan oak.

From the cor. of secs. 4, 5, 8 and 9
North, retracing line bet. secs. 4 and 5.
Descend NE. slope, through heavy timber and dense undergrowth.

- 1.45 Ravine, course SE.; ascend steep SE. slope.
- 12.15 Top of spur, slopes E.; descend NE. slope.
- 29.50 Creek, 2 lks. wide, course E.; ascend.
- 29.60 Trail, bears E. and W.
- 30.80 Ascend bluff, 175 ft. high.
- 33.50 Top of bluffs; continue ascent.
- 34.00 Top of rocky spur, slopes SE.; descend steep NE. slope.
- 38.40 Ravine, course E.; ascend.
- 38.55 Fall 68 lks. E. of the point for old $\frac{1}{4}$ sec. cor. located by reference to the bearing trees. At the exact corner point

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which

- A fir, 7 ins. diam., bears S. 5° E., 43 lks. dist., mkd. $\frac{1}{4}$ S 4 BT. (New B. T.)
- A madrona, 10 ins. diam., bears S. 14° E., 14 lks. dist., mkd. $\frac{1}{4}$ S 4 BT. (Old B. T.)
- A yellow pine, 24 ins. diam., bears N. 71°15' W., 142 lks. dist., mkd. $\frac{1}{4}$ S 5 BT. (New B. T.)

The true course and length of this line is N. 1°00' W., 38.56 chs.

I continue my measurements from the $\frac{1}{4}$ sec. cor. North, surveying the line bet. secs. 4 and 5.

- 43.10 Top of spur, slopes E.; descend.