

Retracement Portion Subdivisions, T. 31 S., R. 7 W.

CHAINS  
40.05

Fall 42 lks. W. of point for old  $\frac{1}{4}$  sec. cor. located by reference to the bearing trees. At the exact corner point

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S\ 6\ | \ S\ 5 \\ 1918 \end{array}$$

from which

A white oak, 10 ins. diam., bears S. 11° E., 28 lks. dist., mkd.  $\frac{1}{4}$  S 5 BT. (Old B. T.)

A white oak, 10 ins. diam., bears S. 83° W., 54 lks. dist., mkd.  $\frac{1}{4}$  S 6 BT. (Old B. T.)

The true course and length of this line is N. 0°36' E., 40.05 chs.

I continue my measurements from the  $\frac{1}{4}$  sec. cor. North, surveying the line bet. secs. 5 and 6.

45.35 Top of spur, slopes W.; descend.

53.25 Creek, 1 lk. wide, course SW.; ascend.

54.35 Top of point, slopes SW.; descend.

65.55 Creek, 5 lks. wide, course SW.; after careful search I find no trace of the old witness corner; ascend over series of bluffs.

71.17 Top of bluffs, bears NE. and SW.

73.05 Trail, bears NE. and SW.

77.90 Intersect the S. bdy. of sec. 31, T. 30 S., R. 7 W., 1.56 chs. S. 89°58' W. of the old cor. of secs. 5 and 6, previously changed to an angle point.

At the point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 5 and 6, with brass cap mkd.

$$\begin{array}{c} S\ 6\ | \ S\ 5 \\ T\ 31\ S\ | \ R\ 7\ W \\ 1918 \end{array}$$

from which

A fir, 14 ins. diam., bears S. 62° 45' E., 101 lks. dist., mkd. T 31 S R 7 W S 5 BT.

A black oak, 6 ins. diam., bears S. 21°15' W., 44 lks. dist., mkd. T 31 S R 7 W S 6 BT.

Land, mountainous.

Soil, gravelly granite loam, 2nd and 3rd rate.

Timber, fir, white oak, black oak, madrona and live oak.

Undergrowth, live oak, fir, arrowwood and tan oak.