

Dependent Resurvey of part of W. Bdy. of T. 22 S., R. 8 W.

CHAINS						
	<p>Note: I had no 1 in. iron post for this cor., but, having 2 in. posts to spare, I monumented the corner with one of them.</p> <p>Thence</p> <p>N. 0° 55' W., on a true line, bet. secs. 19 and 24.</p> <p>Asc. 82 ft. over gentle SE. slope, through dense undergrowth and scattering timber.</p>					
13.50	Ridge, bears E. and W.; desc. 358 ft. over N. slope.					
30.05	Dry wash, course E.; asc. 132 ft. over SE. slope.					
34.75	Spur, slopes E.; desc. 150 ft. over NE. slope.					
39.79	Proportionate point, Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 13, 18, 19, and 24, with brass cap mkd.					
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 22 S</td></tr> <tr><td>R 9 W R 8 W</td></tr> <tr><td>S 13 S 18</td></tr> <tr><td>S 24 S 19</td></tr> <tr><td>1931</td></tr> </table>	T 22 S	R 9 W R 8 W	S 13 S 18	S 24 S 19	1931
T 22 S						
R 9 W R 8 W						
S 13 S 18						
S 24 S 19						
1931						
	from which					
	<p>A cedar, 38 ins. diam., bears N. 51° 45' E., 86 lks. dist., mkd. T 22 S R 8 W S 18 B T.</p> <p>A hemlock, 10 ins. diam., bears S. 48° 30' E., 33 lks. dist., mkd. T 22 S R 8 W S 19 B T.</p> <p>A hemlock, 7 ins. diam., bears S. 49° W., 28 lks. dist., mkd. T 22 S R 9 W S 24 B T.</p> <p>A hemlock, 10 ins. diam., bears N. 76° W., 34 lks. dist., mkd. T. 22 S R 9 W S 13 B T.</p>					
	<p>Land, mountainous. Soil, rocky red clay; 3rd rate. Timber, fir, hemlock, cedar, and maple. Undergrowth, rhododendron, tan oak, alder, madrona, chinquapin, and willow.</p>					
	<p>N. 0° 55' W., on a true line, bet. secs. 13 and 18.</p> <p>Desc. 388 ft. over NE. slope, through dense timber and undergrowth.</p>					
11.20	Creek, 4 lks. wide, course NW.; asc. 282 ft. over SW. slope.					
19.90	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for S. 1/16 sec. cor., with brass cap mkd.					
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>S 1/16</td></tr> <tr><td>S 13 S 18</td></tr> <tr><td>1931</td></tr> </table>	S 1/16	S 13 S 18	1931		
S 1/16						
S 13 S 18						
1931						
	from which					
	<p>A fir, 22 ins. diam., bears N. 0° 45' E., 111 lks. dist., mkd. S 1/16 S 18 B T.</p> <p>A fir, 30 ins. diam., bears S. 61° 30' W., 45 lks. dist., mkd. S 1/16 S 13 B T.</p>					
26.50	Ridge, bears E. and W., 112 ft. above the 1/16 sec. cor.; desc. 338 ft. over N. slope.					